MEGAMAN®

LED LIGHT SOURCE

Product Guide 2026

www.megaman.cc





CONTENTS

ABOUT MEGAMAN®

Who We Are	04
MEGAMAN® Milestones	05
Rigorous Quality and Management Systems	06
Innovative and Unique Products	06
Product Series and GTM Range	07
New ErP & Energy Labelling Regulations	08
Nomenclature	09

TECHNOLOGY

DUAL BEAM TECHNOLOGY	14
U-DIM	15
ULTRA RICH COLOUR	16
DIM TO WARM	17





PRODUCT HIGHLIGHT

DIM TO WARM	18
MEGA EFFICIENCY	20
ULTRA RICH COLOUR (RA97)	22
MELLOTONE 2000K	23

DIRECTIONAL LAMP

AR111	25
PAR16	29
HYBRID FOCUS PAR16	34
MR16	35
PAR20, PAR30L, PAR38	36
R50, R63 & R80	37

NON-DIRECTIONAL LAMP

CLASSIC	38
P45	40
CANDLE	42
GLOBE	44
ST64	47
GX53	48
T-LAMP	49
LILIPUT	50
T100, T120	51
UFO	52



DECORATIVE

GOLDEN FILAMENT	53
G4	54
G9/GU9	55
CROWN SILVER	56
SMOKY FILAMENT	58

GO-TO-MARKET(GTM) SERIES

PAR16	77
LED T8 TUBE	78





TUBE

LED T5 TUBE	59
LED T8 TUBE	61
LED PLUG-IN TUBE	64

SPECIAL APPLICATION

NIGHT LIGHT	65
CLUSTERLITE®	67
LED HID ULTRA	68
LED HID T-LINE	69
PLANT LAMP	70
SENSOR LIGHT	71
RADAR MOTION SENSOR LIGHT	72
MICROWAVE MOTION SENSOR LIGHT	73
HIGH TEMPERATURE LAMP	74
COLD WEATHER LAMP	75

SUPPLEMENTARY

T5-Ballast Compatibility List	79



About MEGAMAN®

Who We Are

Artificial light enhances the way we live and work. It brings us safety, comfort and productivity. Originated in Germany, MEGAMAN® is committed to providing light in a way that is truly sustainable, energy saving and of such a quality that it brings a positive difference into the lives of all who use our innovative LED lighting solutions.

MEGAMAN® is proud to be a major lighting brand to have exclusively manufactured low-energy lighting products throughout its entire history, offering more than 30 years of industry expertise and innovation to the lighting market.

Beginning in 1994 with the highly successful production of CFL light sources, MEGAMAN® has evolved to become a complete low-energy LED lighting solutions provider. MEGAMAN® has built a reputation for producing high-performance LED light sources that offer a true replacement for traditional metal halide and halogen – combining quality lighting performance with substantial energy savings.

MEGAMAN® is now applying its market-leading experience to an even wider range of lighting solutions including revolutionary Smart Lighting System and a suite of integrated LED luminaires.

- *INGENIUM*® ZB Smart Lighting Solution provides further energy saving potential for users and allows them have full control of smart devices via mobile app from anywhere in the world
- An extensive range of LED Luminaires are developed for both indoor and outdoor applications across diverse industries
- MEGAMAN®'s lighting products are distributed throughout the world mainly in Europe, Middle East and Asia
- Our advanced Research and Development facilities will ensure a continuous supply of innovative and sustainable lighting products in the market.

MEGAMAN® continues to play a leading role in combating climate change and carbon emissions by pursuing continuous innovation in the production of low-energy lighting solutions.













MEGAMAN® MILESTONES

2026 Launched MEGAMAN® dimLINK® technology - a simple and cost-effective solution for step dimming control

2024 MEGAMAN® XChange® lighting solution developed as a cross-platform resolution

2023 Launched *INGENIUM*® MATTER smart lighting, works with various platforms

2022 Infinite IoT lighting solution developed based on Bluetooth Low Energy which is widely adopted in smartphones and tablets

2019 Extended product range of *INGENIUM*® ZB smart lighting released

2018 Launched Dual Beam Technology (DBT) which empowers users to have two beam angles in one LED luminaire or lamp

2016 Launched U-DIM™ technology which offers seamless dimming and is compatible with the widest range of existing dimmers

2015 Being one of the first companies to use plastic extrusion to produce water-proof battens; Launched *INGENIUM*® ZB smart lighting solution which adopts Zigbee technology

2014 Launched first smart lighting range, *INGENIUM*® BLU;
Industry first full range of Dim to Warm LED products

2013 Integrated LED luminaires introduced

2012 Patented LED module and light engine - TECOH® MHx and TECOH® CFx
TECOH® CFx - World's first 2000lm Zhaga Book2 Certified Light Engine

2011 High R9 Technology first introduced to LED range

2010 Launched the first MEGAMAN® LED Candle and Classic Lamp

2009 Innovative Thermal Conductive Highway™ (TCH) technology incorporated into MEGAMAN® LED reflectors

2008 – **1999** Revolutionary patents and technologies invented for CFL products including: Patented Cooling-Tube technology, Silicone Protection technology, Award-winning industry first CFL GU10 reflector, Industry first Long Life CFL reaches 15,000 hours lifetime, Dimmable CFLs using DorS Step Dimming and DIMMER*ABLE* Linear Dimming technology, Amalgam technology which prevents the use of liquid mercury.

1997 Industry first candle-shaped CFL launched

1996 Industry first classic-shaped CFL launched

1994 MEGAMAN® incorporated in Germany

RIGOROUS QUALITY AND MANAGEMENT SYSTEMS

All MEGAMAN® products are designed, tested and produced in our own factories in Xiamen, China. Standards have been implemented factory-wide to ensure the MEGAMAN® manufacturing processes deliver innovative, reliable and safe products with high-quality standards now and in the future.

To ensure that MEGAMAN® products comply with the highest quality standards, company manufacturing plants are equipped with their own assembly lines.

The MEGAMAN® business runs under the most stringent management and quality systems. The green elements of the production process are maximised, employee welfare is prioritised and the company is socially responsible to the local community. To continually develop these areas, MEGAMAN® has undertaken a range of international accreditations. These include:

Quality Management System

MEGAMAN® lamps and luminaires are manufactured and certified to ISO 9001:2015, ISO 14001:2015.

Product Quality Assurance

MEGAMAN® lamps and luminaires are made using premium quality materials and innovative technologies within stringent control measures, to deliver maximum performance and energy efficiencies.

CE | TÜVRheinland | DEKRA

CNAS | ISO 9001 | ISO 14001

INNOVATIVE AND UNIQUE PRODUCTS

With our patented LED design and technology, the MEGAMAN® LED products are able to deliver superb performance, including low power consumption, excellent light output and low maintenance costs. They provide the highest quality lighting performance of any LED based product on the market consuming the same power!

A new era in LED lighting solutions.

Unique Features

- Energy efficient replacement for traditional metal halide, CFL, halogen and incandescent lamps
- Deliver superb lighting performance
- High luminous efficacy up to 211lm/W
- High lumen maintenance rated lumen maintenance of 70% (L70) at up to 50,000 hours
- Long rated life up to 50,000 hours
- High colour rendering up to Ra97
- High colour temperature consistency
- Enhanced colour applications of Perfect White, Dim to Warm and RichColour series
- Options of different beam angles for the LED Reflector range
- Up to 96% energy savings
- Simple installation and servicing
- No UV and IR radiation

Additional Benefits

- Mercury-free
- Instant start-up
- Wide range of operating temperatures

Applications

- Boutiques / Shops
- Shopping Malls
- Hotels / Restaurants / Lounges
- Museums
- Galleries
- Offices
- Household



PRODUCT SERIES

As a leading innovator of LED technology, MEGAMAN® has developed an extensive range of LED products for various domestic and commercial applications. Our products are classified into four categories, namely Professional, Smart, Economy and Go-To-Market series. Each series has its own features designed to meet every need of consumers and professionals.



PROFESSIONAL SERIES

Suitable for commercial and high-end interior applications, the Professional series delivers high quality and comfortable light sources. This series possesses the advantages of powerful lighting performance, perfect optical design and excellent colour rendering. Having a similar profile and outlook to traditional halogen lamps, the MEGAMAN® LED reflector in Professional series is designed with unique technology such as our Hybrid Reflector and Dual Beam Technology (DBT) which offers a flexible choice of beam angles in one single luminaire.

SMART SERIES

This series is a value-added option for consumers looking for high quality lighting at affordable prices. Featuring superb light output with high efficacy and performance, the Smart series is an ideal replacement for traditional incandescent or halogen lamps. The benefits of energy savings up to 90% and longer lamp life add to its appeal for consumers.

ECONOMY SERIES

The most economical option among all series which serves an entry-level LED solution to replace halogen, incandescent and CFL lamps. Its long rated lamp life and high energy savings provide all the advantages you expect over traditional lighting products, but with the MEGAMAN® guarantee of quality.

GO-TO-MARKET(GTM) SERIES

MEGAMAN® has newly launched the Go-To-Market (GTM) Series which targets new customers with incentive price. This series underlines the fact that it can be applied from launching new products or even moving a current product into a new market. This is a pricing strategy where the price of a product is initially set low to rapidly reach a wide fraction of the market.









New ErP & Energy Labelling Regulations



Starting from 1 September 2021, the Ecodesign Regulations and Energy Labelling Regulations was updated and ultimate goal is to maintain a sustainable development in lighting industry by a significant energy saving for lighting products and systems.

The Ecodesign Regulations (EU) 2019/ 2020

- Optimizing the design of light sources and seperated control gear for more sustainability and efficiency
- Products that failed to meet the regulatory requirements have already been phased out. For example, halogen lamps with G9, G4, and GY6.35 caps, as well as fluorescent T8 lamps, have been phased out starting from 1 September 2023
- Lighting installation will have to be renovated with new energy-efficient light sources

The Energy Labelling Regulation – empowerment through information

- Introduce a new energy label to empower end users to choose energy efficient products
- New scale reflects how efficient a product is – the definition of A to G will change based on new efficiency requirements.



Upgrade of Nomenclature System

Classic and Special Lamp

Model No. | **Supplementary Code**

LG 200 110 /dm/r9 - OP v00 + E27 + 927 + V0240

Category Name
Two capital letters

EU = LED G4
EX = LED Flexi or LED strip with 305mm length
LC = LED Candle
LG = LED Classic, ST58, Globe, or T-lamp
LJ = LED R7s
LU = LED G9
LF = LED Fire Lamp
LS = LED Crown Silver
LP = LED Plug-in Tube
ST = LED strip with flexible length option

Sequence
Three digits for indication
From 200-99

Wattage
Three digits for indication

045 = 4.5W
110 = 11W
180 = 18W

Technology / Product Feature
Special Feature / Technology - two digits, come with small letter(s) and/or number

Optic Design
Two capital letters

CS = Clear cover
OP = Opal cover
GD = Golden cover
BU = Blue cover
GN = Green cover
OR = Orange cover
RD = Red cover
YL = Yellow cover
TP = Flame tip
GP = Golden cover with Flame tip

Version
One letter two digits

v00 = standard
v10 = special country
v01 = different lumen

First digit: Country
Second digit: Lumen

Lamp Base
Type of lamp base

Examples:
G53
GU10
E27
E14
B22
G4
E26
GX53
GU9
B15d
R7s
GU5.3
E10

Colour Temperature
Three digits for indication

Examples:
927 = CRI>90, 2700K
830 = CRI>80, 3000K

Voltage
last three/four digits for indication

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Product with iBLU technology, start with 'b'		
-	/mt	*INGENIUM*® MATTER
dBT	/b1	*INGENIUM*® BLU Gen 1
dBT2	/b2	*INGENIUM*® BLU Gen 2
Product with iZB technology, start with 'z'		
dZB	/z1	*INGENIUM*® ZB
-	/wf	WIFI
Product with dimming feature, start with 'd'		
d	/dm	U-DIM / Dimmable Compact Dim
w	/dw	Dim to Warm
s	/ds	Step Dimming
Product with colours feature		
p	/pw	Perfect White
R9	/r9	RichColour
ru	/ru	Utlra RichColour
bu	/bu	Blue colour light
gn	/gn	Green colour light
or	/or	Orange colour light
rd	/rd	Red colour light

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Others		
r	/sr	Sensor Light
PT	/pt	Plant Lamp
N/A	/wp	Outdoor version, waterproof
tw	/tw	Tunable white
ec	/ec	Extended colour light (RGBW)
db	/db	Dual Beam Technology (DBT)
sw	/sw	Step-to-Warm
ms	/ms	with microwave motion sensor
ps	/ps	with PIR sensor

Voltage

V0100	AC100	AC012	AC12V
V0110	AC100 - 120V	DC020	DC20V
V0120	AC110 - 120V	DC036	DC36V
V0127	AC100 - 127V	AD012	AC/DC12V
V0240	AC220 - 240V	U0277	AC100 - 277V
AC120	AC120V	U0240	AC100 - 240V
AC220	AC220V	C1050	1050mA

First letter 'V' stands for Voltage
First letter 'U' stands for Universal (Wide voltage)
First two letters 'AC' stands for fixed AC voltage
First two letters 'DC' stands for fixed DC voltage
First two letters 'AD' stands for AC and DC operable
First letter 'C' stands for Current

Upgrade of Nomenclature System

LED Reflector

Model No. | **Supplementary Code**

LR 200 050 /dm/r9 - LN v00 - SP + 024D035D GU10 + 927 + V0240

Category Name
Two capital letters

LR = Integral LED reflector/GX53
ER = LED reflector with external converter

Sequence
Three digits for indication
From 200-999

Wattage
Three digits for indication

032 = 3.2W
050 = 5W
180 = 18W

Technology / Product Feature
Special Feature / Technology - two digits, come with small letter(s) and/or number

Optic Design
Two capital letters

HR = Hybrid reflector
TH = TCH
LN = Optical reflector
DG = Diffuser glass
OP = Opal cover
BU = Blue cover
GN = Green cover
OR = Orange cover
RD = Red cover

Version
One letter two digits

v00 = standard
v10 = special country
v01 = different lumen

First digit: Country
Second digit: Lumen

A compact dim version of LR4605dLN and LR4605.5dDG (which are universal dimming) are developed for MUK. These adapt compact dim circuit but acting as universal dimming for UK dimmer. These versions are decided to provide to MUK only right now. Hence, different country is used to represent in model no. version.

Beam Angle
Two capital letters for indication

Beam Angle
024D035D = 24° <-> 35°
024D045D = 24° <-> 45°

Lamp Base
Type of lamp base

Examples:
GU10
E27
E26
GX53
GU24
E14
GU5.3
B22
E17
G53

Colour Temperature
Three digits for indication

Examples:
927 = CRI>90, 2700K
830 = CRI>80, 3000K

Voltage
last three/four digits for indication

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Product with iBLU technology, start with 'b'		
-	/mt	*INGENIUM*® MATTER
dBT	/b1	*INGENIUM*® BLU Gen 1
dBT2	/b2	*INGENIUM*® BLU Gen 2
Product with iZB technology, start with 'z'		
dZB	/z1	*INGENIUM*® ZB
-	/wf	WIFI
Product with dimming feature, start with 'd'		
d	/dm	U-DIM / Dimmable Compact Dim
w	/dw	Dim to Warm
s	/ds	Step Dimming
Product with colours feature		
p	/pw	Perfect White
R9	/r9	RichColour
ru	/ru	Utlra RichColour
bu	/bu	Blue colour light
gn	/gn	Green colour light
or	/or	Orange colour light
rd	/rd	Red colour light
Others		
r	/sr	Sensor Light
PT	/pt	Plant Lamp
N/A	/wp	Outdoor version, waterproof
tw	/tw	Tunable white
ec	/ec	Extended colour light (RGBW)
db	/db	Dual Beam Technology (DBT)
sw	/sw	Step-to-Warm
ms	/ms	with microwave motion sensor
ps	/ps	with PIR sensor

Voltage

V0100	AC100	AC012	AC12V
V0110	AC100 - 120V	DC020	DC20V
V0120	AC110 - 120V	DC036	DC36V
V0127	AC100 - 127V	AD012	AC/DC12V
V0240	AC220 - 240V	U0277	AC100 - 277V
AC120	AC120V	U0240	AC100 - 240V
AC220	AC220V	C1050	1050mA

First letter 'V' stands for Voltage
First letter 'U' stands for Universal (Wide voltage)
First two letters 'AC' stands for fixed AC voltage
First two letters 'DC' stands for fixed DC voltage
First two letters 'AD' stands for AC and DC operable
First letter 'C' stands for Current

Beam Angle

Existing Suffix	Proposed Suffix	Special Feature / Technology
SP	NS	1-8 (Narrow Spot)
SP	SP	9-15 (Spot)
SP/FL	NF	16-24 (Narrow Flood)
FL/WFL	FL	25-35 (Flood)
WFL	WF	36-45 (Wide Flood)
VWFL	UF	46-60 (Very Wide Flood)
SWFL	SF	>61 (Super Wide Flood)
-	ND	Non-directional
-	2B	Two Beam Angles

Upgrade of Nomenclature System

CLUSTERLITE®

Model No. | **Supplementary Code**

LH 200 046 /dm/r9 - OP v00 + E27 + 927 + V0240

Category Name
Two capital letters

LH = LED CLUSTERLITE®

Sequence
Three digits for indication
From 200-999

Wattage
Three digits for indication

027 = 27W
032 = 32W
046 = 46W

Different to other series, LED CLUSTERLITE® has a unique 'sequence'. Three digits to represent wattage, i.e. 032 means 32W

Technology / Product Feature
Special Feature / Technology - two digits, come with small letter(s) and/or number

Optic Design
Two capital letters

CS = Clear cover
OP = Opal cover

Version
One letter two digits

v00 = standard
v10 = special country
v01 = different lumen

First digit: Country
Second digit: Lumen

A compact dim version of LR4605dLN and LR4605.5dDG(which are universal dimming) are developed for MUK. These adapt compact dim circuit but acting as universal dimming for UK dimmer. These versions are decided to provide to MUK only right now. Hence, different country is used to represent in model no. version.

Lamp Base
Type of lamp base

Examples:
E27

Colour Temperature
Three digits for indication

Examples:
927 = CRI>90, 2700K
830 = CRI>80, 3000K

Voltage
last three/four digits for indication

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Product with iBLU technology, start with 'b'		
-	/mt	*INGENIUM*® MATTER
dBT	/b1	*INGENIUM*® BLU Gen 1
dBT2	/b2	*INGENIUM*® BLU Gen 2
Product with iZB technology, start with 'z'		
dZB	/z1	*INGENIUM*® ZB
-	/wf	WIFI
Product with dimming feature, start with 'd'		
d	/dm	U-DIM / Dimmable Compact Dim
w	/dw	Dim to Warm
s	/ds	Step Dimming
Product with colours feature		
p	/pw	Perfect White
R9	/r9	RichColour
ru	/ru	Utlra RichColour
bu	/bu	Blue colour light
gn	/gn	Green colour light
or	/or	Orange colour light
rd	/rd	Red colour light

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Others		
r	/sr	Sensor Light
PT	/pt	Plant Lamp
N/A	/wp	Outdoor version, waterproof
tw	/tw	Tunable white
ec	/ec	Extended colour light (RGBW)
db	/db	Dual Beam Technology (DBT)
sw	/sw	Step-to-Warm
ms	/ms	with microwave motion sensor
ps	/ps	with PIR sensor

Voltage

V0100	AC100	AC012	AC12V
V0110	AC100 - 120V	DC020	DC20V
V0120	AC110 - 120V	DC036	DC36V
V0127	AC100 - 127V	AD012	AC/DC12V
V0240	AC220 - 240V	U0277	AC100 - 277V
AC120	AC120V	U0240	AC100 - 240V
AC220	AC220V	C1050	1050mA

First letter 'V' stands for Voltage
First letter 'U' stands for Universal (Wide voltage)
First two letters 'AC' stands for fixed AC voltage
First two letters 'DC' stands for fixed DC voltage
First two letters 'AD' stands for AC and DC operable
First letter 'C' stands for Current

Upgrade of Nomenclature System

LED Tube

Model No. | **Supplementary Code**

LT **200** **180** **/mb/r9** - **06** **v00** + **G13** + **930** + **V0240**

Category Name
Two capital letters

LT = Integral LED Tube
T8 , S19 or T5

Sequence
Three digits for indication
From 200-999

Wattage
Three digits for indication

095 = 9.5W
180 = 18W
245 = 24.5W

Special Feature / Technology
Two digits, come with small letter(s) and/or number

Length
Two digits for indication

03 = 300mmL
04 = 450mmL
06 = 600mmL
09 = 900mmL
12 = 1200mmL
15 = 1500mmL
18 = 1800mmL

Version
One letter two digits

v00 = standard
v10 = special country
v01 = different lumen

First digit: Country
Second digit: Lumen

A compact dim version of LR4605dLN and LR4605.5dDG(which are universal dimming) are developed for MUK. These adapt compact dim circuit but acting as universal dimming for UK dimmer. These versions are decided to provide to MUK only right now. Hence, different country is used to represent in model no. version.

Lamp Base
Type of lamp base

Examples:
G13
S19
G5

Colour Temperature
Three digits for indication

Examples:
930 = CRI>90, 3000K
840 = CRI>80, 4000K

Voltage
last three/four digits for indication

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Power source type of LED tube		
U	/us	Universal
L	/ac	Direct line in, AC line voltage
Blank	/mb	Magnetic ballast
-	/eb	Electronic ballast
Others		
R9	/r9	RichColour
-	/ru	Ultra RichColour
-	/bu	Blue colour light
-	/gn	Green colour light
-	/or	Orange colour light
-	/rd	Red colour light
H	/hf	High power factor
-	/tw	Tunable white
-	/ec	Extended colour light (RGBW)
-	/sp	Shatterproof
-	/sf	Shatterproof FEP
r	/ms	with microwave motion sensor
-	/ps	with PIR sensor

Voltage

V0100	AC 100	AC012	AC12V
V0110	AC100 - 120V	DC020	DC20V
V0120	AC110 - 120V	DC036	DC36V
V0127	AC100 - 127V	AD012	AC/DC12V
V0240	AC220 - 240V	U0277	AC100 - 277V
AC120	AC120V	U0240	AC100 - 240V
AC230	AC230V	C1050	1050mA

First letter 'V' stands for Voltage
First letter 'U' stands for Universal (Wide voltage)
First two letters 'AC' stands for fixed AC voltage
First two letters 'DC' stands for fixed DC voltage
First two letters 'AD' stands for AC and DC operable
First letter 'C' stands for Current

Upgrade of Nomenclature System

NIGHT LIGHT



Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Product with iBLU technology, start with 'b'		
dBT	/b1	*INGENIUM*® BLU Gen 1
dBT2	/b2	*INGENIUM*® BLU Gen 2
Product with iZB technology, start with 'z'		
dZB	/z1	*INGENIUM*® ZB
Product with WIFI, start with 'wf'		
-	/wf	WIFI
Product with dimming feature, start with 'd'		
d	/dm	U-DIM / Dimmerable / Compact Dim
w	/dw	Dim to Warm
s	/ds	Step Dimming
Product with colours feature		
p	/pw	Perfect White
R9	/r9	RichColour
-	/ru	Utlra RichColour
-	/bu	Blue colour light
-	/gn	Green colour light
-	/or	Orange colour light
-	/rd	Red colour light

Technology / Product Feature

Existing Suffix	Proposed Suffix	Special Feature / Technology
Others		
r	/sr	Sensor Light
N/A	/wp	Outdoor version, waterproof
-	/tw	Tunable white
-	/ec	Extended colour light (RGBW)
-	/sw	Step-to-Warm
r	/ms	with microwave motion sensor
-	/pr	with PIR sensor

DBT

DUAL BEAM TECHNOLOGY

Two beam angles in one luminaire

MEGAMAN® pioneered an innovative approach for switching the size of the light spot with a simple push action on luminaires featured with Dual Beam Technology. With this technology one can shape the light spot of the luminaire from a narrow beam to a wider beam angle.

The term “Dual Beam” refers to the dual function of a luminaire. It can be set to project a narrow beam or a wider beam. Luminaires with “Dual Beam” function provide users unparalleled flexibility and convenience when adjusting the contrast between ambient and accent lighting on-site, eliminating the hustle and bustle of changing luminaire with a different beam angle. In some cases, fixtures with specific beam angle are not readily available and subsequent arrangement will cause inevitable delay in completing projects. Choosing luminaires equipped with MEGAMAN®'s Dual Beam Technology will put you at ease when doing projects.



How it works

The mechanism that makes Dual Beam illumination possible is cleverly engineered into the DBT-enabled luminaire. To shape the beam angle of such luminaire, simply apply a push action on the front lens. This unique mechanism enables users to switch beam angles instantly from a narrow beam to a wider beam and vice versa.

Let us take one luminaire model as an example. As shown below, the default beam angle setting is 24° (the len is in an extended position - Fig 1). By applying a push action on the front lens, users can adjust the beam angle to as broad as 36° or 45° (subject to model number) as the front lens is pushed to a retracted position - Fig 2.



Fig 1: The lens in extended position, producing narrow beam light effect.
Fig 2: The lens in retracted position, producing wider beam light effect.



U-DIM™

Flicker free dimming compatible with widest range of existing dimmers



With the phase out of high-energy consuming traditional light sources, lighting manufacturers have a responsibility to make it as easy as possible for consumers to make the switch to LED lighting. It is with this in mind that MEGAMAN® has developed a revolutionary U-DIM™ technology that makes switching to LED easy.

Over the years traditional light sources have required different types of dimmers depending on their technology. The revolution that LED brings to lighting by replacing all types of conventional sources means a universal solution is required for LED to dim on all these existing circuits.

Up to now, when replacing traditional lamps with LED, working with an incompatible dimmer may have caused a multitude of issues from flickering to failure. MEGAMAN® lamps with U-DIM™ is a breakthrough in dimming technology and makes our lamps compatible with the widest possible range of existing dimmers, whether they are Leading-edge or Trailing Edge. It is easy to use, you just 'plug & play' so it takes the headache out of upgrading your lighting scheme. MEGAMAN® U-DIM™ also allows superior performance, flicker-free dimming from 100% right down to just 5%; combine this with our latest Dim to Warm technology and you can even have the exact same warmth as halogen when dimmed for a cosy ambience.

U-DIM™ technology will be offered as standard with MEGAMAN® lamps using eye-catching hybrid reflector technology. With mains voltage halogen reflector lamps being phased out in the EU from September 1st 2016, this means you can rely on MEGAMAN® LEDs to replace your halogen lamps in terms of dimming compatibility, performance and aesthetics, while benefiting from the energy-savings offered by LED technology.

Leading-edge and Trailing-edge are the most popular dimmers used for conventional light sources. They work by chopping out parts of the voltage and reducing power to the light source in order to achieve the dimming performance.

Leading-edge

also known as 'forward-phase control dimmers, 'triac dimmers' or 'incandescent dimmers'

Leading-edge dimmer switches were used originally to dim incandescent and halogen lamps magnetic low voltage transformers.



Trailing-edge

also known as 'reverse-phase control dimmer' or 'electronic dimmers'

Trailing-edge dimmers are traditionally used for electronic drivers or low voltage transformers (capacitive loads).



RICHCOLOUR

MEGAMAN® RichColour is a range of LED lamps designed to maximise the richness and quality of colours. With high colour rendering of Ra90 or above, MEGAMAN® RichColour is the perfect LED replacement for halogen lamps in applications where the faithful colour reproduction associated with natural light is crucial. These places include retail stores, art galleries and museums.

ULTRA RICHCOLOUR

Taking colour enhancement yet a step further, MEGAMAN® Ultra RichColour combines all the benefits of standard RichColour technology with even better colour rendering quality of up to Ra97, featuring enhanced red colour rendition (R9) of ≥75 - maximising the visual impact of meat, fresh fruit and vegetables. The well-balanced and high quality light of Ultra RichColour lamps makes them the perfect choice for food and other display lighting applications where the visual appeal of items is essential.





TSC	Appearance under daylight	Sample
R1	Light greyish red	
R2	Dark greyish yellow	
R3	Strong yellow green	
R4	Moderate yellowish green	
R5	Light bluish green	
R6	Light blue	
R7	Light violet	
R8	Light reddish purple	
R9	Strong red	
R10	Strong yellow	
R11	Strong green	
R12	Strong blue	
R13	Light yellowish pink	
R14	Moderate olive green	

Figure 1 Test Colour Sample



When we determine the general colour rendering index, the first eight colours in the Test Colour Sample (TCS; see Figure 1) defined in accordance with DIN 6169 are employed for the calculation. In addition to these eight colours (R1 to R8), there are another six colours (R9 to R14) that are more vivid and known as “saturated” colours.

The MEGAMAN® Ultra RichColour lamp not only has high colour rending index of Ra97 and a high red colour rendition (R9) value of ≥75, but it also has a high value of the other “saturated” colours (R10 to R14), which allows the beautiful red of an object to be revealed and creates well-balanced and high-quality lighting.

Dim to WARM
1800K < 2700K

DIM TO WARM

Improved dimming performance with the warmth of halogen

MEGAMAN® is proud to be the first to introduce a wide range of LED products incorporating a brand new Dim to Warm technology. These LED lamps emit a warmer light when they are dimmed. The colour temperature of these LED lamps changes from 2700K to 1800K when the lamps are dimmed from 100% to 5% (from 100% to 1% for LED AR111 and LED MR16 constant current types), perfectly simulating the characteristics of incandescent and halogen lamps.

Unlike many products on the market which use multiple lens arrays, MEGAMAN®'s Dim to Warm lamps contain a unique single circuit chip level technical solution, allowing them to have the same compact profile as incandescent and halogen lamps while also replicating their warmth and dimming curve. The MEGAMAN® LED lamps with the Dim to Warm feature are true replacements for incandescent and halogen lamps in terms of the outlook, size, lighting effect and produce lighting performance that is familiar to consumers.





MEGAMAN® Dim to Warm is the LED lamp that dims like traditional light sources. Moving through a wide colour temperature range of 2800K (2700K) to 1800K as the lamps dim from 100% to 10%, the close replication of the dimming curve of halogen and incandescent makes MEGAMAN® Dim to WARM a unique offering to the LED market.



Dim to WARM 1800K < 2700K

DIM TO WARM



Product Features

- Dim-to-Warm technology improved dimming performance and options available to perfectly simulate the characteristics of incandescent and halogen lamps
- Offers perfect linear dimming which is compatible with most leading-edge and trailing-edge EU dimmers
- LED emit a warmer light when the lamps are dimmed from 100% to 5%
- RichColour (CRI≥ 90) & Ultra RichColor (CRI≥ 97) dim-to-warm lamps maximize colour richness
- Up to 89% instant energy savings compared to traditional light bulbs
- Low maintenance costs thanks to extremely long lifetime up to 40,000 hours



1



2


3


4



5

Model No.	Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
U-DIM™														
LG7105wR9	E27	5	N/A	N/A	470	N/A	2700K-1800K	Ra90	25000	Ø60 x 109	100-5%	F	Smart	1
LG7108.2wR9	E27	8.2	N/A	N/A	470	N/A	2700K-1800K	Ra90	25000	Ø60 x 109	100-5%	F	Smart	1
LG2602.9wR9	E14	2.9	N/A	N/A	250	N/A	2700K-1800K	Ra90	25000	Ø45 x 87	100-5%	F	Smart	2
LG2605.5wR9	E14	5.5	N/A	N/A	470	N/A	2700K-1800K	Ra90	25000	Ø45 x 87	100-5%	F	Smart	2
LC0402.9wR9	E14	2.9	N/A	N/A	250	N/A	2700K-1800K	Ra90	25000	Ø35 x 100	100-5%	F	Smart	3
LC0405.5wR9	E14	5.5	N/A	N/A	470	N/A	2700K-1800K	Ra90	25000	Ø35 x 100	100-5%	F	Smart	3
LR057050/dw/r9-HRv00-WF	GU10	5	680	36	410	345	3000K-1800K	Ra90	25000	Ø50 x 55	100-5%	G	Smart	4
LR212100/dw/db/ru-HRv00-2B +024D045D SDCM ≤4	GU10	10	3800 (24º) 1600 (45º)	24/45	680 (24º) 720 (45º)	620 (24º) 660 (45º)	3000K-1800K	Ra97	40000	Ø111 x 82	100-5%	G	Pro	5

1800K < 2700K
Dim to WARM

DIM TO WARM





DBT



6



7

Model No.	Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable														
ER205120/dw/db/ru/HRv00-2B+024D045D*	G53	12	4500 (24º) 2000 (45º)	24/45	920 (24º) 970 (45º)	880 (24º) 920 (45º)	3000K-1800K	Ra97	40000	Ø111 x 58	100-1%	G	Pro	6
ER200065/dw/ru-HRv00-WF*	GU5.3	6.5	1200	36	430	400	3000K-1800K	Ra97	40000	Ø50 x 46	100-1%	G	Pro	7

ER200065/dw/ru-HRv00-WF* 350mA (DC16-20V)

ER205120/dw/db/ru/HRv00-2B+024D045D* 350mA (DC34V)

* Capable of linear dimming when working with DALI, DSI or 1-10V dimming drivers, and the dimming performance depends on the specification of driver.

MEGA EFFICIENCY

MEGA EFFICIENCY



MEGAMAN® introduces the first MEGAMAN® **MEGA EFFICIENCY** with Energy Class A LED bulbs, these innovative LED bulbs meet the stringent EU Eco-design and Energy Labelling regulations, which came into effect on 1 September, 2021. Under the new regulations, only lighting products that achieve an energy efficiency of 210lm/W can be rated as EU Energy Class A. This means that these new Class A bulbs consume up to 53% less energy compared with LED lamps, to achieve the same light output and quality as standard MEGAMAN® LED bulbs. With the extra-long life time 50,000 hours making MEGAMAN® **MEGA EFFICIENCY** LED bulbs provide extremely high luminous efficiency of up to 211lm/W under 2700K. MEGAMAN® **MEGA EFFICIENCY** – LED bulbs are the best choice of LED bulbs to save energy and costs and are leading the way to a brighter, greener future for our Earth.

Product Features

- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations (A ↑ G)
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours

220-240V



Type	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Filament													
Non-Dimmable													
A60	40	LG6102.3CS	E27	2.3	485	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
A60	60	LG9804CS	E27	4	840	2700K	80	50000	Ø60 x 104	N/A	A	Pro	2
A60	75	LG9805CS	E27	5	1055	2700K	80	50000	Ø60 x 104	N/A	A	Pro	2
A60	100	LG231072-CSv00	E27	7.2	1521	2700K	80	50000	Ø60 x 104	N/A	A	Pro	3
P45	25	LG232012-CSv00	E14	1.2	252	2700K	80	50000	Ø45 x 79	N/A	A	Pro	4
P45	40	LG232023-CSv00	E14	2.3	485	2700K	80	50000	Ø45 x 79	N/A	A	Pro	4
Candle	25	LG232012-CSv00	E14	1.2	255	2700K	80	50000	Ø35 x 97	N/A	A	Pro	5
Candle	40	LC208023-CSv00	E14	2.3	485	2700K	80	50000	Ø35 x 97	N/A	A	Pro	5
G95	60	LG06804CS	E27	4	840	2700K	80	50000	Ø95 x 137	N/A	A	Pro	6
G95	75	LG06805CS	E27	5	1055	2700K	80	50000	Ø95 x 137	N/A	A	Pro	6
G125	100	LG069072-CSv00 NEW	E27	7.2	1521	2700K	80	50000	Ø124 x 172	N/A	A	Pro	7
ST64	60	LG225023-CSv00	E27	2.3	485	2700K	80	50000	Ø64 x 140	N/A	A	Pro	8
ST64	75	LG226040-CSv00	E27	4	840	2700K	80	50000	Ø64 x 140	N/A	A	Pro	9

MEGA EFFICIENCY



1

220-240V

Type	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
360° Illumination													
Non-Dimmable													
A60	40	LG295023-0Pv00	E27	2.3	485	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
A60	60	LG295040-0Pv00	E27	4	840	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
A60	75	LG295050-0Pv00	E27	5	1055	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
A60	100	LG295072-0Pv00	E27	7.2	1521	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1



2

220-240V

Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
PAR16 Glass													
Non-Dimmable													
LR6302.1LN-WFL	2.1	700	36	430	375	2700K	80	50000	Ø50 x 55	N/A	A	Pro	2

ULTRA RICHCOLOUR



Product Features

- MEGAMAN® Ultra RichColour is the perfect choice for display lighting applications where the visual appeal of items is essential, thanks to the richness and quality of colours, especially red colour rendition (R9) of >75
- Offers perfect linear dimming which is compatible with most popular leading and trailing EU dimmers
- Low maintenance costs thanks to extremely long lifetime up to 25,000 hours
- Low flickering ratio ≤ 8%



220-240V

Model No.	Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
U-DIM™														
A60														
LG7108.8dru	E27	8.8	N/A	N/A	810	N/A	2700K	Ra97	25000	Ø60 x 109	100-10%	F	Pro	1
CANDLE														
LC0405.5dru	E14	5.5	N/A	N/A	470	N/A	2700K	Ra97	25000	Ø35 x 100	100-10%	F	Pro	2
P45														
LG2605.5dru	E14	5.5	N/A	N/A	470	N/A	2700K	Ra97	25000	Ø45 x 87	100-10%	F	Pro	3
PAR16 Glass														
LR6304.7druLN-WFL	GU10	4.7	600	36	410	345	2700K	Ra97	25000	Ø50 x 55	100-10%	F	Pro	4
PAR16 Plastic														
LR057047/dm/ru-HRv00-WF	GU10	4.7	600	36	410	345	2700K	Ra97	25000	Ø50 x 55	100-10%	F	Pro	5



TSC	Appearance under daylight	Sample
R1	Light greyish red	
R2	Dark greyish yellow	
R3	Strong yellow green	
R4	Moderate yellowish green	
R5	Light bluish green	
R6	Light blue	
R7	Light violet	
R8	Light reddish purple	
R9	Strong red	
R10	Strong yellow	
R11	Strong green	
R12	Strong blue	
R13	Light yellowish pink	
R14	Moderate olive green	

Figure 1 Test Colour Sample



2000K MELLOTONE





Product Features

- The special colour temperature of 2000K MELLOTONE, create a warm, soft and comfortable atmosphere
- High CRI90 to maximize the richness and quality of colours
- MELLOTONE emits a warmer colour temperature, which is less attractive to many insects compared to cooler white colour temperature
- Dimmable 100% - 10% to save energy and change the visual appearance and mood of space



220-240V

Lamp Type	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable												
P45	LG305029/dm/r9-0Pv00	E14	2.9	250	2000K	Ra90	25000	Ø45 x 77	100-10%	F	Smart	1
P45	LG306055/dm/r9-0Pv00	E14	5.5	470	2000K	Ra90	25000	Ø45 x 91	100-10%	F	Smart	2
Candle	LC217032/dm/r9-0Pv00	E14	3.2	250	2000K	Ra90	25000	Ø37 x 100	100-10%	G	Smart	3
Candle	LC218060/dm/r9-0Pv00	E14	6	470	2000K	Ra90	25000	Ø37 x 107	100-10%	G	Smart	4
A60	LG307090/dm/r9-0Pv00	E27	9	810	2000K	Ra90	25000	Ø60 x 107	100-10%	F	Smart	5
A60	LG268120/dm/r9-0Pv00	E27	12	1055	2000K	Ra90	25000	Ø60 x 121	100-10%	F	Smart	6



220-240V

Lamp Type	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Non-Dimmable													
P45	LG222025-GDv00	NEW	E14	2.5	200	2000K	Ra80	15000	Ø45 x 84	N/A	G	Econ	1
Candle	LC207025-GDv00	NEW	E14	2.5	200	2000K	Ra80	15000	Ø35 x 100	N/A	G	Econ	2
A60	LG230042-GDv00	NEW	E27	4.2	380	2000K	Ra80	15000	Ø60 x 105	N/A	F	Econ	3
G95	LG6807.5GD	NEW	E27	4.2	380	2000K	Ra80	15000	Ø95 x 135	N/A	F	Econ	4
G125	LG6907.5GD	NEW	E27	4.2	380	2000K	Ra80	15000	Ø125 x 168	N/A	F	Econ	5
ST64	LG227075-GDv00	NEW	E27	4.2	380	2000K	Ra80	15000	Ø64 x 143	N/A	F	Econ	6

2000K MELLOTONE





220-240V

Work well under fire-rated downlights at Ta45°C

Lamp Type	Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series
PAR16	LR232045/dm/r9-HRv00-WF	4.5	650	36	410	345	2000K	Ra90	25000	Ø50 x 55	100-10%	F	Smart



220-240V

6kV SURGE PROTECTION

Lamp Type	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Operating Temperature	Dimension (mm)	Energy Label	Series
Passive Cooling											
Clusterlite	LH200024-OPv00	E27	24.5	2900	2000K	80	50000	-30ºC to +60ºC	Ø63 x 196	E	Pro

The LED CLUSTERLITE® is not water resistant. The waterproof performance of the lamp would only be attained if the lamp is used with a light fitting with an IP rating of IP44 or above.
The ambient temperature inside the fixture must not exceed 60°C, which is equivalent to a minimum volume of 120x360x220(mm).



220-240V

Eq. Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series
Non-Dimmable											
70W	LG500020-OPv00	NEW	E27	20	2000	2000K	80	25000	Ø75 x 151	F	Smart



220-240V

Eq. Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Diameter (mm)	Energy Label	Series
Non-Dimmable											
100W	LG504021-OPv00	NEW	E27	20	2700	2000K	80	25000	Ø38 x 170	E	Smart

AR111





Product Features

- Simple push action on AR111 featured with Dual Beam Technology (DBT) can shape the light spot of the lamp from a narrow beam 24° to a wider beam angle 45°
- Comprehensive Professional series of LED AR111 reflectors for 50W, 75W and 100W halogen AR111 replacement with DBT technology which increases functionality and flexibility for different environments
- Offers perfect linear dimming which is compatible with most leading-edge and trailing-edge EU dimmers
- Ultra RichColour (CRI 97) maximizes the richness and quality of colours, especially red colour rendition (R9) of > 75
- Dim-to-Warm options available to perfectly simulate the characteristics of incandescent and halogen lamps in terms of the outlook, size, and lighting effect to offer lighting performance that is familiar to consumers
- Extremely long lifetime of 40,000 hours
- Colour Consistency SDCM ≤ 4


1


2


3

220-240V

DBT

Input	Model No.	Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dual Beam Technology SDCM ≤4															
Dim To Warm															
220-240V	LR212100/dw/db/ru-HRv00-2B+024D045D	GU10	10	3800 (24°) 1600 (45°)	24/45	680 (24°) 720 (45°)	620 (24°) 660 (45°)	3000K-1800K	Ra97	40000	Ø111 x 82	100-5%	G	Pro	1
350mA (DC34V)	ER205120/dw/db/ru-HRv00-2B+024D045D	G53	12	4500 (24°) 2000 (45°)	24/45	920 (24°) 970 (45°)	880 (24°) 920 (45°)	3000K-1800K	Ra97	40000	Ø111 x 58	100-1%	G	Pro	2
U-DIM™															
220-240V	LR212110/dm/db/ru-HRv00-2B+024D045D	GU10	11	3600 (24°) 1500 (45°)	24/45	800 (24°) 870 (45°)	720 (24°) 780 (45°)	2700K	Ra97	40000	Ø111 x 82	100-5%	G	Pro	1
220-240V	LR212110/dm/db-HRv00-2B+024D045D	GU10	11	5000 (24°) 2000 (45°)	24/45	980 (24°) 1070 (45°)	870 (24°) 950 (45°)	2700K	80	40000	Ø111 x 82	100-5%	F	Pro	1
Dimmable															
AC12V	ER205115/dm/db-HRv00-2B+024D045D	G53	11.5	5000 (24°) 2000 (45°)	24/45	1000 (24°) 1050 (45°)	900 (24°) 950 (45°)	2700K	80	40000	Ø111 x 58	100-10%	F	Pro	2
Hybrid Reflector															
U-DIM™															
220-240V	LR6509.5dR9HR-75H08D	GU10	9.5	13000	8	650	590	2700K	Ra90	40000	Ø111 x 82	100-5%	G	Pro	3

AR111





LR212110/dm/db/ru-HRv00-2B+024D



m	Lux	Ø cm
0.5	14400	22
1	3600	44
1.5	1600	67
2	900	89

Beam angle = 24°

LR212110/dm/db-HRv00-2B+024D



m	Lux	Ø cm
0.5	20000	21
1	5000	43
1.5	2222	64
2	1250	85

Beam angle = 24°

ER205115/dm/db-HRv00-2B+024D



m	Lux	Ø cm
0.5	20000	21
1	5000	43
1.5	2222	64
2	1250	85

Beam angle = 24°

LR212110/dm/db/ru-HRv00-2B+045D



m	Lux	Ø cm
0.5	6000	41
1	1500	83
1.5	667	124
2	375	166

Beam angle = 45°

LR212110/dm/db-HRv00-2B+045D



m	Lux	Ø cm
0.5	8000	41
1	2000	83
1.5	889	124
2	500	166

Beam angle = 45°

ER205115/dm/db-HRv00-2B+045D



m	Lux	Ø cm
0.5	8000	41
1	2000	83
1.5	889	124
2	500	166

Beam angle = 45°

ER205120/dw/db/ru-HRv00-2B+024D



m	Lux	Ø cm
0.5	18000	21
1	4500	43
1.5	2000	64
2	1125	85

Beam angle = 24°

LR6509.5dR9HR-75H08D



m	Lux	Ø cm
0.5	52000	7
1	13000	14
1.5	5778	21
2	3250	28

Beam angle = 8°

ER205120/dw/db/ru-HRv00-2B+045D



m	Lux	Ø cm
0.5	8000	41
1	2000	83
1.5	889	124
2	500	166

Beam angle = 45°

AR111





Product Features

- Offer two different LED AR111 solutions that can be driven by a halogen transformer for direct retrofit, as well as in-line voltage for easy maintenance
- Various beam angle options available, especially for the narrow beam 8° by means of Hybrid Focus Technology
- High CRI90 to maximize the richness and quality of colours
- Long lifetime up to 25,000 hours
- Ideal for use in any retail outlet, reception area, hotel, restaurant, gallery or residential application


1


2


3


4

220-240V | **12V**

Input	Model No.		Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable																
220-240V	LR239095/dm/r9-HRv00-NS	NEW	GU10	9.5	10500	8°	950	690	2700K	Ra90	25000	Ø111 x 72	100-10%	F	Smart	1
220-240V	LR239095/dm/r9-HRv00-NF	NEW	GU10	9.5	1650	24°	950	690	2700K	Ra90	25000	Ø111 x 76	100-10%	F	Smart	2
220-240V	LR239095/dm/r9-HRv00-WF	NEW	GU10	9.5	850	45°	950	690	2700K	Ra90	25000	Ø111 x 76	100-10%	F	Smart	2
12V	ER210095/dm/r9-HRv00-NS	NEW	G53	9.5	10000	8°	850	650	2700K	Ra90	25000	Ø111 x 62	100-10%	G	Smart	3
12V	ER210095/dm/r9-HRv00-NF	NEW	G53	9.5	1500	24°	850	650	2700K	Ra90	25000	Ø111 x 67	100-10%	G	Smart	4
12V	ER210095/dm/r9-HRv00-WF	NEW	G53	9.5	700	45°	850	650	2700K	Ra90	25000	Ø111 x 67	100-10%	G	Smart	4

AR111





LR239095/dm/r9-HRv00-NS



m	Lux	Ø cm
0.5	42000	7
1	10500	14
1.5	4667	21
2	2625	28

Beam angle = 8°

LR239095/dm/r9-HRv00-NF



m	Lux	Ø cm
0.5	6600	21
1	1650	43
1.5	733	64
2	413	85

Beam angle = 24°

LR239095/dm/r9-HRv00-WF



m	Lux	Ø cm
0.5	3400	41
1	850	83
1.5	378	124
2	213	166

Beam angle = 45°

ER210095/dm/r9-HRv00-NS



m	Lux	Ø cm
0.5	40000	7
1	10000	14
1.5	4444	21
2	2500	28

Beam angle = 8°

ER210095/dm/r9-HRv00-NF



m	Lux	Ø cm
0.5	6000	21
1	1500	43
1.5	667	64
2	375	85

Beam angle = 24°

ER210095/dm/r9-HRv00-WF



m	Lux	Ø cm
0.5	2800	41
1	700	83
1.5	311	124
2	175	166

Beam angle = 45°

DBT PAR16



Product Features

- Simple push action on PAR16 featured with Dual Beam Technology (DBT) can shape the light spot of the lamp from a narrow beam to a wider beam angle, including 24° to 35°, 40º to 60º
- Perfectly designed as replacement for traditional halogen lamps which deliver a sport light to create the desired atmosphere
- Offer perfect linear dimming which is compatible with most leading-edge and trailing-edge EU dimmers
- Enhance efficacy, beam control and excellent optics by Hybrid Reflector Technology
- Captivating appearance by all glass integrated design
- Various beam angle options available, including 24°, 36°, 40º, 60° and 100°
- Work well under fire rated downlights with the life time up to 25,000 hours at 45°C
- Up to 92% instant energy saving compared to 50W halogen lamps



1



2

220-240V

Work well under fire-rated downlights at Ta45°C

Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dual Beam Technology													
U-DIM™													
LR211052/dm/db-HRv00-2B+024D035D	5.2	2550 (24°) 1650 (35°)	24/35	430	400	2700K	80	25000	Ø50 x 56	100-5%	F	Pro	1
LR211052/dm/db-HRv00-2B+040D060D	5.2	900 (40°) 420 (60°)	40/60	430	400	2700K	80	25000	Ø50 x 56	100-5%	F	Pro	2
LR211053/dm/db-HRv00-2B+024D035D	5.3	3000 (24°) 1800 (35°)	24/35	550	500	2700K	80	25000	Ø50 x 56	100-5%	E	Pro	1

DBT PAR16

PHOTOMETRIC DATA



LR211052/dm/db-HRv00-2B+024D



m	Lux	Ø cm
0.5	10200	21
1	2550	43
1.5	1133	64
2	638	85

Beam angle = 24°

LR211052/dm/db-HRv00-2B+035D



m	Lux	Ø cm
0.5	6600	32
1	1650	63
1.5	733	95
2	413	126

Beam angle = 35°

LR211052/dm/db-HRv00-2B+040D



m	Lux	Ø cm
0.5	3600	36
1	900	73
1.5	400	109
2	225	146

Beam angle = 40°

LR211052/dm/db-HRv00-2B+060D



m	Lux	Ø cm
0.5	1680	58
1	420	115
1.5	187	173
2	105	231

Beam angle = 60°

LR211053/dm/db-HRv00-2B+024D



m	Lux	Ø cm
0.5	12000	21
1	3000	43
1.5	1333	64
2	750	85

Beam angle = 24°

LR211053/dm/db-HRv00-2B+035D



m	Lux	Ø cm
0.5	7200	32
1	1800	63
1.5	800	95
2	450	126

Beam angle = 35°

PAR16





- Ultra RichColour (CRI 97) maximizes the richness and quality of colours, especially red colour rendition (R9) of > 75
- Dim-to-Warm options available to perfectly simulate the characteristics of incandescent and halogen lamps in terms of the outlook, size, and lighting effect to offer lighting performance that is familiar to consumers


1


2


3


4

220-240V

Work well under fire-rated downlights at Ta45°C

Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Plastic (Non-DBT)													
Dim To Warm													
LR057050/dw/r9-HRv00-WF	5	680	36	410	345	3000K-1800K	Ra90	25000	Ø50 x 55	100-5%	G	Smart	1
U-DIM™													
LR057047/dm/ru-HRv00-WF	4.7	600	36	410	345	2700K	Ra97	25000	Ø50 x 55	100-10%	F	Pro	1
Dimmable													
LR057033/dm-HRv00-WF	3.3	650	36	410	345	2700K	80	25000	Ø50 x 55	100-10%	E	Smart	1
LR057041/dm-HRv00-WF	4.1	900	36	500	430	2700K	80	25000	Ø50 x 55	100-10%	E	Smart	1
LR232045/dm/r9-HRv00-WF	4.5	650	36	410	345	2000K	Ra90	25000	Ø50 x 55	100-10%	F	Smart	2
Non-Dimmable													
LR057033-HRv00-WF	3.3	680	36	410	345	2700K	80	15000	Ø50 x 55	N/A	E	Econ	1
LR057059-HRv00-SF	5.9	300	100	600	500	2700K	80	25000	Ø50 x 55	N/A	F	Econ	3
High lumen GU10 Dimmable													
LR232050/dm-HRv00-NF	5	1600	24	650	550	2700K	80	25000	Ø50 x 55	100-10%	E	Smart	4
LR232050/dm-HRv00-WF	5	1200	36	700	600	2700K	80	25000	Ø50 x 56	100-10%	D	Smart	2
LR232045/dm-HRv00-SF	4.5	350	90	600	520	2700K	80	25000	Ø50 x 55	100-10%	D	Smart	4

PAR16







5

220-240V

Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Glass (Non-DBT)													
U-DIM™													
LR6304.7druLN-WFL	4.7	600	36	410	345	2700K	Ra97	25000	Ø50 x 55	100-10%	F	Pro	5
Dimmable													
LR6304.7dLN-WFL	4.7	650	36	390	345	2700K	80	15000	Ø50 x 55	100-10%	F	Smart	5
LR6304.9dLN-WFL	4.9	800	36	520	450	2700K	80	15000	Ø50 x 55	100-10%	F	Smart	5
Non-Dimmable													
LR6302.1LN-WFL	2.1	700	36	400	375	2700K	80	50000	Ø50 x 55	N/A	A	Pro	5
LR6301.9LN-WFL	1.9	350	36	190	140	2700K	80	15000	Ø50 x 55	N/A	F	Econ	5
LR6303.1LN-WFL	3.1	450	36	270	230	2700K	80	15000	Ø50 x 55	N/A	F	Econ	5
LR6304.7LN-WFL	4.7	650	36	390	345	2700K	80	15000	Ø50 x 55	N/A	F	Econ	5
LR6304.9LN-WFL	4.9	800	36	520	450	2700K	80	15000	Ø50 x 55	N/A	F	Econ	5

PAR16

PHOTOMETRIC DATA



LR057033/dm-HRv00-WF



m	Lux	Ø cm
0.5	2720	32
1	680	65
1.5	302	97
2	170	130

Beam angle = 36°

LR232055/dm-HRv00-WF



m	Lux	Ø cm
0.5	3600	32
1	900	65
1.5	400	97
2	225	130

Beam angle = 36°

LR057033-HRv00-WF



m	Lux	Ø cm
0.5	2000	32
1	500	65
1.5	222	97
2	125	130

Beam angle = 36°

LR057050/dw/r9-HRv00-WF



m	Lux	Ø cm
0.5	2720	32
1	680	65
1.5	302	97
2	170	130

Beam angle = 36°

LR057072-HRv00-ND



m	Lux	Ø cm
0.5	1160	119
1	290	238
1.5	129	358
2	73	477

Beam angle = 100°

LR6304.7dLN-WFL



m	Lux	Ø cm
0.5	2400	32
1	600	65
1.5	267	97
2	150	130

Beam angle = 36°

LR6306.2dLN-WFL



m	Lux	Ø cm
0.5	3200	32
1	800	65
1.5	356	97
2	200	130

Beam angle = 36°

LR6301.9LN-WFL



m	Lux	Ø cm
0.5	1400	32
1	350	65
1.5	156	97
2	88	130

Beam angle = 36°

LR6303.1LN-WFL



m	Lux	Ø cm
0.5	1800	32
1	450	65
1.5	200	97
2	113	130

Beam angle = 36°

LR6304.7LN-WFL



m	Lux	Ø cm
0.5	2600	32
1	650	65
1.5	289	97
2	163	130

Beam angle = 36°

LR6304.9LN-WFL



m	Lux	Ø cm
0.5	3200	32
1	800	65
1.5	356	97
2	200	130

Beam angle = 36°

LR057059-HRv00-SF



m	Lux	Ø cm
0.5	4800	119
1	1200	238
1.5	533	358
2	300	477

Beam angle = 100°

LR232045/dm/r9-HRv00-WF



m	Lux	Ø cm
0.5	1400	32
1	350	65
1.5	156	97
2	88	130

Beam angle = 36°

LR232050/dm-HRv00-WF



m	Lux	Ø cm
0.5	4800	32
1	1200	65
1.5	533	97
2	300	130

Beam angle = 36°

LR237045/dm-HRv00-SF



m	Lux	Ø cm
0.5	1400	119
1	350	238
1.5	156	358
2	88	477

Beam angle = 90°

LR237050/dm-HRv00-FL



m	Lux	Ø cm
0.5	10200	21
1	2550	43
1.5	1133	64
2	638	85

Beam angle = 24°

HYBRID FOCUS PAR16





Product Features

- With advance Hybrid Focus technology, MEGAMAN® develops an ultra-narrow beam angle 6º & 12º GU10
- High CRI90 to maximize the richness and quality of colours
- Prefect for any applications that require precision lighting to highlight the object



1



2

220-240V

Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable													
LR237050/dm/r9-HRv00-NS	5	7000	6	410	345	2700K	Ra90	25000	Ø50 x 55	100-10%	G	Smart	1
LR237060/dm/r9-HRv00-SP	6	5000	12	560	460	2700K	Ra90	25000	Ø50 x 54	100-10%	F	Smart	2

LR237050/dm/r9-HRv00-NS



LR237060/dm/r9-HRv00-SP





MR16





Product Features

- MEGAMAN® LED MR16 reflector has the same compact profile as halogen MR16 and delivers superb lighting performance, excellent light efficiency and better glare control for both accent and ambient lighting applications
- Ultra RichColour (CRI 97) maximizes the richness and quality of colours, especially red colour rendition (R9) of > 75
- Dim-to-Warm options available to perfectly simulate the characteristics of incandescent and halogen lamps in terms of the outlook, size, and lighting effect to offer lighting performance that is familiar to consumers
- Constant current MR16 works with DALI, DSI, 1-10V dimming drivers, it works with MEGAMAN® driver which drive 3pcs of lamp with synchronized start-up time
- Work well with AC 12V halogen transformers and generate much less heat
- Extremely long lifetime up to 40,000 hours


1


2


3

Input	Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Plastic														
Dim To Warm														
350mA (DC16-20V)	ER200065/dw/ru-HRv00-WF	6.5	1200	36	430	400	3000K-1800K	Ra97	40000	Ø50 x 46	100-1%	G	Pro	1
Constant Current														
350mA (DC16-20V)	ER200065/dm-HRv00-WF*	6.5	1800	36	700	650	2700K	80	35000	Ø50 x 46	100-1%	F	Pro	1
Dimmable														
AC 12V	ER045044/dm-LNv00-WF	4.4	700	36	410	345	2700K	80	15000	Ø50 x 46	100-10%	F	Smart	3
AC 12V	ER203080/dm-HRv00-WF	8	1800	36	600	500	2700K	80	25000	Ø50 x 46	100-10%	F	Smart	1
Non-Dimmable														
12V	ER208029-HRv00-WF	2.9	550	36	250	230	2700K	80	15000	Ø50 x 46	N/A	F	Econ	2
12V	ER208044-HRv00-WF	4.4	700	36	390	345	2700K	80	15000	Ø50 x 46	N/A	F	Econ	2
12V	ER208057-HRv00-WF	5.7	800	36	530	450	2700K	80	15000	Ø50 x 46	N/A	F	Econ	2
Glass														
Non-Dimmable														
12V	ER045029-LNv00-WF	2.9	500	36	290	230	2700K	80	15000	Ø50 x 46	N/A	F	Econ	3
12V	ER045044-LNv00-WF	4.4	700	36	410	345	2700K	80	15000	Ø50 x 46	N/A	F	Econ	3
12V	ER045057-LNv00-WF	5.7	800	36	530	450	2700K	80	15000	Ø50 x 46	N/A	F	Econ	3

Constant Current Driver Specification

Category	Model No.	Main Input Voltage (V)	Output Voltage (V)	Max. System Wattage (W)	Rated Life (hrs)	Power Factor (λ)	Width (mm)	Length (mm)	Height (mm)	Dimmable
1X Driver	LD0509x1d-C350	220-240V	DC16-24V	9	50000	>0.9	46	62	20	100-5%
3X Driver	LD205021/dm-C0350		DC30-60V	21			55	116	25	

* Capable of linear dimming when working with DALI, DSI or 1-10V dimming drivers, and the dimming performance depends on the specification of driver.

PAR20, PAR30L, PAR38





Product Features

- Enhance efficacy, beam control and excellent optics by Hybrid Reflector Technology
- IP65-rated available outdoor use
- Dimmable version is available in PAR38, allowing users to adjust brightness level from 100% to 10%
- Life time up to 25,000 hours
- Beam angle 36°



220-240V

IP65 rated outdoor version

Lamp Type	Model No.	Lamp Base	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable															
PAR30L	LR228110/dm-HRv00-WF	E27	11	2000	36	1200	1000	3000K	80	25000	Ø95 x 105	100-10%	E	Smart	2
PAR38	LR229160/dm-HRv00-WF	E27	16	3000	36	1850	1600	3000K	80	25000	Ø120 x 135	100-10%	E	Smart	3
Non-Dimmable															
PAR20	LR227070-HRv00-WF	E27	7	1300	36	800	660	3000K	80	25000	Ø63 x 90	N/A	E	Econ	1
PAR30L	LR228110-HRv00-WF	E27	11	2100	36	1300	1050	3000K	80	25000	Ø95 x 105	N/A	E	Econ	2
PAR38	LR229160-HRv00-WF	E27	16	3000	36	1850	1600	3000K	80	25000	Ø120 x 135	N/A	E	Econ	3

R50, R63, R80





Product Features

- The MEGAMAN® LED R50, R63 and R80 delivers impressive spot lighting which a perfect retrofit replacement for halogen or incandescent spots
- Plastic and glass versions with different beam angle options are available for various applications
- Dimmable version available for glass version, allowing users to adjust brightness level from 100% to 10%
- Compatible with existing fixture with E27 and E14 holders
- Flicker Free ≤ 3% for non-dimmable version provides maximum visual comfort



220-240V **Plastic Version**

Lamp Type	Model No.	Lamp Base	Wattage (W)	Beam Angle (°)	Max. Luminous Intensity (cd)	Lumen (lm)	Luminous Flux in 90° Cone (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Non-Dimmable														
R50	LR216014-HRv00-WF	E14	1.4	36	270	110	104	2700K	80	15000	Ø50 x 81	F	Econ	1
R50	LR216026-OPv00-ND	E14	2.6	100	N/A	250	N/A	2700K	80	15000	Ø50 x 81	F	Econ	2
R50	LR216027-HRv00-WF	E14	2.7	36	450	205	196	2700K	80	15000	Ø50 x 81	F	Econ	1
R50	LR216049-OPv00-ND	E14	4.9	100	N/A	470	N/A	2700K	80	15000	Ø50 x 81	F	Econ	2
R63	LR217049-OPv00-ND	E27	4.9	100	N/A	470	N/A	2700K	80	15000	Ø63 x 102	F	Econ	3
R80	LR218086-OPv00-ND	E27	8.6	100	N/A	810	N/A	2700K	80	15000	Ø80 x 110	F	Econ	4



220-240V **Glass Version**

Lamp Type	Model No.	Lamp Base	Wattage (W)	Beam Angle (°)	Max. Luminous Intensity (cd)	Lumen (lm)	Luminous Flux in 90° Cone (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable															
R50	LR219030/dm-OPv00-WF	E14	3.0	36	430	310	250	2700K	80	15000	Ø50 x 82	100 –10%	F	Smart	5
R63	LR220042/dm-OPv00-WF	E27	4.2	36	630	410	345	2700K	80	15000	Ø63 x 102	100 –10%	F	Smart	6
R80	LR221040/dm-OPv00-WF	E27	4.0	36	700	410	345	2700K	80	15000	Ø80 x 110	100 –10%	F	Smart	7
Non-Dimmable															
R50	LR219016-OPv00-WF	E14	1.6	36	200	125	104	2700K	80	15000	Ø50 x 82	N/A	G	Econ	5
R50	LR219032-OPv00-WF	E14	3.2	36	360	220	196	2700K	80	15000	Ø50 x 82	N/A	G	Econ	5
R63	LR220033-OPv00-WF	E27	3.3	36	400	235	207	2700K	80	15000	Ø63 x 102	N/A	G	Econ	6
R63	LR220045-OPv00-WF	E27	4.5	36	630	410	345	2700K	80	15000	Ø63 x 102	N/A	F	Econ	6
R80	LR221044-OPv00-WF	E27	4.4	36	750	410	345	2700K	80	15000	Ø80 x 110	N/A	F	Econ	7
R80	LR221085-OPv00-WF	E27	8.5	36	950	810	667	2700K	80	15000	Ø80 x 110	N/A	F	Econ	7

CLASSIC





Product Features

- Perfect LED replacement for halogen lamps in applications
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- Options of RichColour (CRI ≥ 97) in dimmable versions available to maximize colour richness
- High luminous efficacy up to 171lm/W which offers instant energy savings of up to 89% compared to traditional lamps
- High lumen output up to 2900lm
- Low maintenance costs thanks to extremely long lifetime up to 25,000 hours



220-240V | **DC12V**

Input	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dim To Warm													
220-240V	40	LG7105wR9	E27	4.9	470	2700K-1800K	Ra90	25000	Ø60 x 109	100-5%	F	Smart	1
220-240V	60	LG7108.2wR9	E27	8.2	810	2700K-1800K	Ra90	25000	Ø60 x 109	100-5%	F	Smart	1
Standard Bulb													
U-DIM™													
220-240V	60	LG7108.8dru	E27	8.8	810	2700K	Ra97	25000	Ø60 x 109	100-10%	F	Pro	1
Dimmable													
220-240V	40	LG7105.5d	E27	5.5	470	2700K	80	25000	Ø60 x 109	100-10%	F	Smart	1
220-240V	60	LG7108.5d	E27	8.5	810	2700K	80	25000	Ø60 x 109	100-10%	F	Smart	1
220-240V	60	LG307090/dm/r9-0Pv00	E27	9	810	2000K	Ra90	25000	Ø60 x 106	100-10%	F	Smart	2
220-240V	75	LG7108.7d	E27	8.7	1055	2700K	80	25000	Ø60 x 109	100-10%	E	Smart	1
220-240V	60	LG268120/dm/r9-0Pv00	E27	12	1055	2000K	Ra90	25000	Ø60 x 120	100-10%	F	Smart	4
220-240V	100	LG200127/dm-0Pv00	E27	12.7	1521	2700K	80	25000	Ø60 x 114	100-10%	E	Smart	3
220-240V	125	LG268150/dm-0Pv00	E27	15	2050/2150	2700K/4000K	80	25000	Ø60 x 120	100-10%	D	Smart	4
220-240V	150	LG268159/dm-0Pv00	E27	15.9	2452/2552	2700K/4000K	80	25000	Ø60 x 120	100-10%	D	Smart	4
Non-Dimmable													
220-240V	40	LG7104.8	E27	4.8	470	2700K	80	15000	Ø60 x 106	N/A	F	Econ	2
DC12V	40	LG7105+DC012	E27	5	470	2700K	80	15000	Ø60 x 109	N/A	F	Econ	1
220-240V	40	LG7106.1	E27	6.1	600	2700K	80	15000	Ø60 x 106	N/A	F	Econ	2
220-240V	60	LG7108.6	E27	8.6	810	2700K	80	15000	Ø60 x 106	N/A	F	Econ	2
220-240V	75	LG7109	E27	9	1055	2700K	80	15000	Ø60 x 109	N/A	E	Econ	1
220-240V	100	LG200133-0Pv00	E27	13.3	1521	2700K	80	15000	Ø60 x 114	N/A	E	Econ	3
220-240V	125	LG268150-0Pv00	E27	15	2050/2150	2700K/4000K	80	15000	Ø60 x 120	N/A	D	Econ	4
220-240V	150	LG268165-0Pv00	E27	16.5	2452/2552	2700K/4000K	80	15000	Ø60 x 120	N/A	D	Econ	4
220-240V	165	LG268170-0Pv00	E27	17	2752/2900	2700K/4000K	80	15000	Ø60 x 120	N/A	C	Econ	4
High Temperature Lamp													
Dimmable													
220-240V	60	LG7106dv3	E27	6	810	2700K	80	25000	Ø60 x 110	100-10%	D	Smart	5
Non-Dimmable													
220-240V	40	LG7104.5v3	E27	4.5	470	2700K	80	25000	Ø60 x 109	N/A	F	Smart	1
220-240V	60	LG7107v3	E27	7	810	2700K	80	25000	Ø60 x 109	N/A	E	Smart	1
Cold Weather Lamp													
Non-Dimmable													
220-240V	40	LG7108.6v2	E27	8.6	810	2700K	80	15000	Ø60 x 106	N/A	F	Smart	2
220-240V	60	LG7109v2	E27	9	1055	2700K	80	15000	Ø60 x 109	N/A	E	Smart	1

CLASSIC





Product Features

- 360° light illumination with uniform light distribution and high quality lighting performance
- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations (A A↑G)
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours


1


2


3


4

220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
360° Illumination												
Dimmable												
60	LG206042/dm-OPv00	E27	4.2	470	2700K	80	15000	Ø60 x 104	100-10%	E	Smart	1
75	LG206072/dm-OPv00	E27	7.2	810	2700K	80	15000	Ø60 x 104	100-10%	E	Smart	1
100	LG206085/dm-OPv00	E27	8.5	1055	2700K	80	15000	Ø60 x 104	100-10%	E	Smart	1
100	LG206110/dm-OPv00	E27	11	1521	2700K	80	15000	Ø60 x 104	100-10%	D	Smart	1
Non-Dimmable												
40	LG295023-OPv00	E27	2.3	485	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
60	LG295040-OPv00	E27	4	840	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
75	LG295050-OPv00	E27	5	1055	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
100	LG295072-OPv00	E27	7.2	1521	2700K	80	50000	Ø60 x 104	N/A	A	Pro	1
40	LG206040-OPv00	E27	4	470	2700K	80	15000	Ø60 x 104	N/A	E	Econ	1
60	LG206067-OPv00	E27	6.7	810	2700K	80	15000	Ø60 x 104	N/A	E	Econ	1
75	LG206085-OPv00	E27	8.5	1055	2700K	80	15000	Ø60 x 104	N/A	E	Econ	1
100	LG206110-OPv00	E27	11	1521	2700K	80	15000	Ø60 x 104	N/A	D	Econ	1
Filament												
Dimmable												
40	LG6103.4dCS NEW	E27	3.4	470	2700K	80	15000	Ø60 x 104	100-10%	D	Smart	2
60	LG9805.9dCS NEW	E27	5.9	810	2700K	80	15000	Ø60 x 104	100-10%	D	Smart	3
75	LG9807.8dCS	E27	7.8	1055	2700K	80	15000	Ø60 x 104	100-10%	D	Smart	3
100	LG9811dCS	E27	11	1521	2700K	80	15000	Ø60 x 104	100-10%	D	Smart	3
Non-Dimmable												
40	LG6102.3CS	E27	2.3	485	2700K	80	50000	Ø60 x 104	N/A	A	Pro	2
60	LG9804CS	E27	4	840	2700K	80	50000	Ø60 x 104	N/A	A	Pro	3
75	LG9805CS	E27	5	1055	2700K	80	50000	Ø60 x 104	N/A	A	Pro	3
100	LG231072-CSv00	E27	7.2	1521	2700K	80	50000	Ø60 x 104	N/A	A	Pro	4
40	LG6103.4CS NEW	E27	3.4	470	2700K	80	15000	Ø60 x 104	N/A	D	Econ	2
60	LG9805.9CS NEW	E27	5.9	810	2700K	80	15000	Ø60 x 104	N/A	D	Econ	3
75	LG9807.8CS	E27	7.8	1055	2700K	80	15000	Ø60 x 104	N/A	D	Econ	3
100	LG9811CS	E27	11	1521	2700K	80	15000	Ø60 x 104	N/A	D	Econ	3

P45





Product Features

- Perfect LED replacement for halogen lamps and incandescent lamps in applications where the faithful colour reproduction associated with natural light is crucial
- Dim to Warm technology allow dimming control by dimmer and normal ON/OFF switch respectively
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- Options of RichColour (CRI ≥ 97) in dimmable versions available to maximize colour richness
- High efficacy of up to 128lm/W
- Up to 90% instant energy savings compared to traditional light bulbs
- Long lifetime up to 25,000 hours



220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Standard Bulb												
Dim To Warm												
40	LG2602.9wR9	E14	2.9	250	2700K-1800K	Ra90	25000	Ø45 x 87	100-5%	F	Smart	1
60	LG2605.5wR9	E14	5.5	470	2700K-1800K	Ra90	25000	Ø45 x 87	100-5%	F	Smart	1
U-DIM™												
40	LG2605.5dru	E14	5.5	470	2700K	Ra97	25000	Ø45 x 87	100-10%	F	Pro	1
Dimmable												
25	LG2602.9d	E14	2.9	250	2700K	80	25000	Ø45 x 87	100-10%	F	Smart	1
25	LG305029/dm/r9-0Pv00	E14	2.9	250	2000K	Ra90	25000	Ø45 x 79	100-10%	F	Smart	4
40	LG2605.5d	E14	5.5	470	2700K	80	25000	Ø45 x 87	100-10%	F	Smart	1
40	LG306055/dm/r9-0Pv00	E14	5.5	470	2000K	Ra90	25000	Ø45 x 90	100-10%	F	Smart	5
Non-Dimmable												
15	LG2601.6	E14	1.6	136	2700K	80	15000	Ø45 x 82	N/A	F	Econ	2
25	LG2602.9	E14	2.9	250	2700K	80	15000	Ø45 x 82	N/A	F	Econ	2
40	LG2604.9	E14	4.9	470	2700K	80	15000	Ø45 x 82	N/A	F	Econ	2
60	LG221077-0Pv00	E14	7.7	810	2700K	80	15000	Ø45 x 82	N/A	F	Econ	3

P45





Product Features

- 360° light illumination with uniform light distribution and high quality lighting performance
- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations (A)
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours


1


2


3

220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
360° Illumination												
Dimmable												
40	LG204042/dm-0Pv00	E14	4.2	470	2700K	80	15000	Ø45 x 79	100-10%	E	Smart	1
Non-Dimmable												
15	LG204012-0Pv00	E14	1.2	136	2700K	80	15000	Ø45 x 79	N/A	E	Econ	1
25	LG204021-0Pv00	E14	2.1	250	2700K	80	15000	Ø45 x 79	N/A	E	Econ	1
40	LG204040-0Pv00	E14	4	470	2700K	80	15000	Ø45 x 79	N/A	E	Econ	1
60	LG204068-0Pv00	E14	6.8	810	2700K	80	15000	Ø45 x 79	N/A	E	Econ	1
Filament												
Dimmable												
40	LG9603.4dCS NEW	E14	3.4	470	2700K	80	15000	Ø45 x 79	100-10%	D	Smart	2
Non-Dimmable												
25	LG232012-CSv00	E14	1.2	252	2700K	80	50000	Ø45 x 79	N/A	A	Pro	3
40	LG232023-CSv00	E14	2.3	485	2700K	80	50000	Ø45 x 79	N/A	A	Pro	3
25	LG9601.8CS NEW	E14	1.8	250	2700K	80	15000	Ø45 x 79	N/A	D	Econ	2
40	LG9603.4CS NEW	E14	3.4	470	2700K	80	15000	Ø45 x 79	N/A	D	Econ	2
60	LG232059-CSv00	E14	5.9	810	2700K	80	15000	Ø45 x 79	N/A	D	Econ	3

CANDLE





Product Features

- Perfect LED replacement for halogen lamps incandescent lamps in applications where the faithful colour reproduction associated with natural light is crucial
- Dim to Warm technology allow dimming control by dimmer and normal ON/OFF switch respectively
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- Options of RichColour (CRI ≥ 97) in dimmable versions available to maximize colour richness
- Ideal for decorative fixtures with filament design
- High efficacy of up to 128lm/W
- Up to 89% instant energy savings compared to traditional light bulbs
- Long lifetime up to 25,000 hours



220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Standard Bulb												
Dim To Warm												
25	LC0402.9wR9	E14	2.9	250	2700K-1800K	Ra90	25000	Ø35 x 100	100-5%	F	Smart	1
40	LC0405.5wR9	E14	5.5	470	2700K-1800K	Ra90	25000	Ø35 x 100	100-5%	F	Smart	1
U-DIM™												
40	LC0405.5dru	E14	5.5	470	2700K	Ra97	25000	Ø35 x 100	100-10%	F	Pro	1
Dimmable												
25	LC0402.9d	E14	2.9	250	2700K	80	25000	Ø35 x 100	100-10%	F	Smart	1
25	LC217032/dm/r9-OPv00	E14	3.2	250	2000K	Ra90	25000	Ø37 x 100	100-10%	G	Smart	4
40	LC0405.5d	E14	5.5	470	2700K	80	25000	Ø35 x 100	100-10%	F	Smart	1
40	LC218060/dm/r9-OPv00	E14	6	470	2000K	Ra90	25000	Ø37 x 107	100-10%	G	Smart	5
Non-Dimmable												
15	LC0401.6	E14	1.6	136	2700K	80	15000	Ø35 x 96	N/A	F	Econ	2
25	LC0402.9	E14	2.9	250	2700K	80	15000	Ø35 x 96	N/A	F	Econ	2
40	LC0404.9	E14	4.9	470	2700K	80	15000	Ø35 x 96	N/A	F	Econ	2
60	LC206077-OPv00	E14	7.7	810	2700K	80	15000	Ø37 x 107	N/A	F	Econ	3

CANDLE





Product Features

- 360° light illumination with uniform light distribution and high quality lighting performance
- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations (A ↑ G)
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours



220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
360° Illumination												
Dimmable												
40	LC200042/dm-0Pv00	E14	4.2	470	2700K	80	15000	Ø35 x 97	100-10%	E	Smart	1
Non-Dimmable												
25	LC200021-0Pv00	E14	2.1	250	2700K	80	15000	Ø35 x 97	N/A	E	Econ	1
40	LC200040-0Pv00	E14	4	470	2700K	80	15000	Ø35 x 97	N/A	E	Econ	1
60	LC200068-0Pv00	E14	6.8	810	2700K	80	15000	Ø35 x 97	N/A	E	Econ	1
Filament												
Dimmable												
40	LC208040/dm-CSv00 NEW	E14	4	470	2700K	80	15000	Ø35 x 97	100-10%	D	Smart	2
Non-Dimmable												
25	LG232012-CSv00	E14	1.2	255	2700K	80	50000	Ø35 x 97	N/A	A ↑ G	Pro	4
40	LC208023-CSv00	E14	2.3	485	2700K	80	50000	Ø35 x 97	N/A	A ↑ G	Pro	4
25	LC1401.8TP NEW	E14	1.8	250	2700K	80	15000	Ø35 x 121	N/A	D	Econ	3
25	LC1401.8CS NEW	E14	1.8	250	2700K	80	15000	Ø35 x 97	N/A	D	Econ	2
40	LC0403.4CS NEW	E14	3.4	470	2700K	80	15000	Ø35 x 97	N/A	D	Econ	3
60	LC208059-CSv00	E14	5.9	810	2700K	80	15000	Ø35 x 97	N/A	D	Econ	4

GLOBE





Product Features

- Perfect LED replacement for halogen lamp in applications
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- Uniformity of light distribution and high quality lighting performance
- High efficacy over 111lm/W
- Up to 90% instant energy savings compared to traditional light bulbs
- Extra-long lifetime up to 25000 hours



1



2

220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Standard Globe												
Dimmable												
75	LG285095/dm-OPv00	E27	9.5	1055	2700K	80	25000	Ø95 x 137	100-10%	E	Smart	1
100	LG285135/dm-OPv00	E27	13.5	1521	2700K	80	25000	Ø95 x 137	100-10%	E	Smart	1
75	LG286095/dm-OPv00	E27	9.5	1055	2700K	80	25000	Ø120 x 159	100-10%	E	Smart	2
100	LG286135/dm-OPv00	E27	13.5	1521	2700K	80	25000	Ø120 x 159	100-10%	E	Smart	2
114	LG286160/dm-OPv00	E27	16	1800	2700K	80	25000	Ø120 x 159	100-10%	E	Smart	2
Non-Dimmable												
60	LG285070-OPv00	E27	7	810	2700K	80	15000	Ø95 x 137	N/A	E	Econ	1
75	LG285095-OPv00	E27	9.5	1055	2700K	80	15000	Ø95 x 137	N/A	E	Econ	1
100	LG285135-OPv00	E27	13.5	1521	2700K	80	15000	Ø95 x 137	N/A	E	Econ	1
75	LG286095-OPv00	E27	9.5	1055	2700K	80	15000	Ø120 x 159	N/A	E	Econ	2
100	LG286135-OPv00	E27	13.5	1521	2700K	80	15000	Ø120 x 159	N/A	E	Econ	2
114	LG286160-OPv00	E27	16	1800	2700K	80	15000	Ø120 x 159	N/A	E	Econ	2

GLOBE





Product Features

- 360° light illumination with uniform light distribution and high quality lighting performance
- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations (A ATG)
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours



1 2

220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
360° Illumination												
Dimmable												
75	LG237085/dm-OPv00	E27	8.5	1055	2700K	80	15000	Ø95 x 137	100-10%	E	Smart	1
100	LG237110/dm-OPv00	E27	11	1521	2700K	80	15000	Ø95 x 137	100-10%	D	Smart	1
75	LG238085/dm-OPv00	E27	8.5	1055	2700K	80	15000	Ø124 x 172	100-10%	E	Smart	2
100	LG238110/dm-OPv00	E27	11	1521	2700K	80	15000	Ø124 x 172	100-10%	D	Smart	2
Non-Dimmable												
60	LG237068-OPv00	E27	6.8	810	2700K	80	15000	Ø95 x 137	N/A	E	Econ	1
75	LG237085-OPv00	E27	8.5	1055	2700K	80	15000	Ø95 x 137	N/A	E	Econ	1
100	LG237110-OPv00	E27	11	1521	2700K	80	15000	Ø95 x 137	N/A	D	Econ	1
75	LG238088-OPv00	E27	8.5	1055	2700K	80	15000	Ø124 x 172	N/A	E	Econ	2
100	LG238110-OPv00	E27	11	1521	2700K	80	15000	Ø124 x 172	N/A	D	Econ	2

GLOBE







1 2

220-240V

Eq.Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Filament													
Dimmable													
60	LG068059/dm-CSv00	NEW	E27	5.9	810	2700K	80	15000	Ø95 x 137	100-10%	D	Smart	1
75	LG068078/dm-CSv00		E27	7.8	1055	2700K	80	15000	Ø95 x 137	100-10%	D	Smart	1
100	LG068011/dm-CSv00		E27	11	1521	2700K	80	15000	Ø95 x 137	100-10%	D	Smart	1
75	LG069078/dm-CSv00		E27	7.8	1055	2700K	80	15000	Ø124 x 172	100-10%	D	Smart	2
100	LG069110/dm-CSv00		E27	11	1521	2700K	80	15000	Ø124 x 172	100-10%	D	Smart	2
Non-Dimmable													
60	LG06804CS		E27	4	840	2700K	80	50000	Ø95 x 137	N/A	A	Pro	1
75	LG06805CS		E27	5	1055	2700K	80	50000	Ø95 x 137	N/A	A	Pro	1
100	LG069072-CSv00	NEW	E27	7.2	1521	2700K	80	50000	Ø124 x 172	N/A	A	Pro	2
60	LG068059-CSv00	NEW	E27	5.9	810	2700K	80	15000	Ø95 x 137	N/A	D	Econ	1
75	LG068078-CSv00	NEW	E27	7.8	1055	2700K	80	15000	Ø95 x 137	N/A	D	Econ	1
100	LG068110-CSv00	NEW	E27	11	1521	2700K	80	15000	Ø95 x 137	N/A	D	Econ	1
75	LG069078-CSv00	NEW	E27	7.8	1055	2700K	80	15000	Ø124 x 172	N/A	D	Econ	2
100	LG069011-CSv00	NEW	E27	11	1521	2700K	80	15000	Ø124 x 172	N/A	D	Econ	2

ST64





Product Features

- Perfectly designed as replacement for incandescent lamps which deliver a warm and cosy atmosphere by clear filament lamps
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- 360° light illumination with uniform light distribution and high quality lighting performance
- Extremely high luminous efficiency up to 211lm/W under 2700K
- Reach the highest level of the latest Energy Labelling regulations ()
- Consumes up to 53% less energy compared with LED lamp
- Extra-long life time to 50,000 hours



1



2

220-240V

Eq.Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Filament													
Dimmable													
40	LG225034/dm-CSv00	NEW	E27	3.4	470	2700K	80	15000	Ø64 x 140	100-10%	D	Smart	1
60	LG226059/dm-CSv00	NEW	E27	5.9	810	2700K	80	15000	Ø64 x 140	100-10%	D	Smart	2
Non-Dimmable													
60	LG225023-CSv00		E27	2.3	485	2700K	80	50000	Ø64 x 140	N/A		Pro	1
75	LG226040-CSv00		E27	4	840	2700K	80	50000	Ø64 x 140	N/A		Pro	2
40	LG225034-CSv00	NEW	E27	3.4	470	2700K	80	15000	Ø64 x 140	N/A	D	Econ	1
60	LG226059-CSv00	NEW	E27	5.9	810	2700K	80	15000	Ø64 x 140	N/A	D	Econ	2

GX53





Product Features

- MEGAMAN® LED GX53 provides an integral LED solution for narrow surface mounted luminaries and recessed fittings of general and ambient lightings
- Compact dimension with low profile design
- Both dimmable and non-dim version are available
- Even light distribution and soft lighting
- High efficacy of up to 106lm/W



220-240V

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Dimension (mm)	Rated Life (hrs)	Dimmable	Energy Label	Series
Dimmable										
LR209049/dm-OPv00-ND	GX53	4.9	480	2700K	80	Ø75 x 24	25000	100-10%	F	Smart
Non-Dimmable										
LR209032-OPv00-ND	GX53	3.2	300	2700K	80	Ø75 x 24	15000	N/A	F	Econ
LR209049-OPv00-ND	GX53	4.9	520	2700K	80	Ø75 x 24	15000	N/A	F	Econ
LR209070-OPv00-ND	GX53	7	700	2700K	80	Ø75 x 24	15000	N/A	F	Econ

T-LAMP





Product Features

- MEGAMAN® LED T-lamp delivers the same light output as its 40W incandescent counterpart, but consumes at least far less energy, allowing this series to be the ideal light source for domestic refrigerators and for general decorative purposes
- Dimmable and non-dim version available
- Even light distribution and soft lighting



220-240V | **DC12V**

Input	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Standard Bulb													
Dimmable													
220-240V	11	LG271020/dm-0Pv00	E14	2.0	100	2700K	80	25000	Ø25 x 59	100-10%	G	Smart	1
Non-Dimmable													
220-240V	5	LG234006-0Pv00	E14	0.6	50	2700K	80	15000	Ø25 x 50	N/A	G	Econ	2
DC12V	10	LG234010-0Pv00+DC012	E14	1.0	90	2700K	80	15000	Ø25 x 50	N/A	F	Econ	2
220-240V	10	LG234011-0Pv00	E14	1.1	90	2700K	80	15000	Ø25 x 50	N/A	G	Econ	2
220-240V	15	LG234016-0Pv00	E14	1.6	136	2700K	80	15000	Ø25 x 50	N/A	F	Econ	2
220-240V	20	LG271021-0Pv00	E14	2.1	200	2700K	80	15000	Ø25 x 59	N/A	F	Econ	1
Filament													
Non-Dimmable													
220-240V	11	LG235011-CSv00	E14	1.1	100	2200K	80	15000	Ø25 x 57	N/A	F	Econ	3
220-240V	25	LG236021-CSv00	E14	2.1	250	2700K	80	15000	Ø25 x 85	N/A	E	Econ	4
220-240V	40	LG236040-CSv00	E14	4	470	2700K	80	15000	Ø25 x 85	N/A	E	Econ	4

LILIPUT





Product Features

- Easy plug-and-play installation without any additional wiring
- Direct retrofit replacement of existing compact fluorescent lamps
- Durable polycarbonate construction
- No toxic chemicals such as mercury which could be released with broken fluorescent lamps
- Energy Class D
- Life time up to 30,000 hours
- Delivers an expansive 120° beam angle, providing broader light coverage and enhanced visual comfort in any setting



220-240V

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Dimension (mm)	Rated Life (hrs)	Energy Label	Photo
Non-Dimmable										
40	LG269049-0Pv00	E27	4.9	470	2700K	80	Ø38 x 116	15000	F	1
48	LG269066-0Pv00	E27	6.6	600	2700K	80	Ø38 x 116	15000	F	1
60	LG269088-0Pv00	E27	8.8	810	2700K	80	Ø38 x 116	15000	F	1
75	LG270105-0Pv00	E27	10.5	1055	2700K	80	Ø45 x 138	15000	F	2
100	LG270138-0Pv00	E27	13.8	1521	2700K	80	Ø45 x 138	15000	E	2
60	LG315070-0Pv01 NEW	G24d	7	810	2700K	80	Ø36 x 105	15000	E	3
75	LG315085-0Pv00 NEW	G24d	8.5	1055	2700K	80	Ø36 x 105	15000	D	3

T100, T120





Product Features

- High luminous efficacy up to 125lm/W which offers instant energy savings of up to 86% compared to traditional lamps
- High lumen output up to 4000lm
- Work with both AC and DC input (DC-Emergency-Systems)
- Flicker free ≤ 3% provides maximum visual comfort



1

220-240V

Input	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Non-Dimmable												
220-240V	170 (3000K/4000K/6500K)	LG276240-0Pv00	E27	24.0	2850 (3000K) 3000 (4000K) 3000 (6500K)	3000K/4000K/6500K	80	15000	Ø100 x 157	E	Econ	1



2

220-240V

Input	Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Non-Dimmable												
220-240V	200 (3000K/4000K/6500K)	LG277340-0Pv00	E27	34.0	3800 (3000K) 4000 (4000K) 4000 (6500K)	3000K/4000K/6500K	80	15000	Ø118 x 178	E	Econ	2

UFO





Product Features

- Wider illumination area for E27 base socket on ceilings
- Simple, compact in size & very easy installation
- Three sizes of selections, high lumen up to 2850lm
- High efficacy with Energy Class E to cater for different applications


1


2


3

220-240V

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
LG329012-0Pv00 NEW	E27	12	1320/1400	3000K/4000K	80	25000	Ø125 x 78	N/A	E	Econ	1
LG293160-0Pv00	E27	16	1700/1800	3000K/4000K	80	25000	Ø150 x 80	N/A	E	Econ	2
LG294240-0Pv00	E27	24	2700/2850	3000K/4000K	80	25000	Ø200 x 95	N/A	E	Econ	3

GOLDEN FILAMENT





Product Features

- Golden Filament offers a ultra-warm and cosy atmosphere
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- 360° light illumination with uniform light distribution and high quality lighting performance
- Ideal for decorative fixtures with filament design
- Up to 91% instant energy savings compared to traditional light bulbs



220-240V

Lamp Type	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable												
Candle	LC212042/dm-GDv00	E14	4.2	400	2500K	80	15000	Ø35 x 97	100-10%	F	Smart	1
P45	LG266042/dm-GDv00	E14	4.2	400	2500K	80	15000	Ø45 x 79	100-10%	F	Smart	2
A60	LG265042/dm-GDv00	E27	4.2	400	2500K	80	15000	Ø60 x 104	100-10%	F	Smart	3
A60	LG230072/dm-GDv00	E27	7.2	660	2500K	80	15000	Ø60 x 104	100-10%	F	Smart	4
G95	LG263042/dm-GDv00	E27	4.2	400	2500K	80	15000	Ø95 x 137	100-10%	F	Smart	5
G120	LG264042/dm-GDv00	E27	4.2	400	2500K	80	15000	Ø124 x 172	100-10%	F	Smart	6
ST64	LG262042/dm-GDv00	E27	4.2	400	2500K	80	15000	Ø64 x 140	100-10%	F	Smart	7
ST64	LG227072/dm-GDv00	E27	7.2	660	2500K	80	15000	Ø64 x 140	100-10%	F	Smart	8

G4





Product Features

- MEGAMAN® LED G4 utilizes advanced sub-miniature LED technology, which gives the series same sparkling effects and form as halogen G4, making it an ideal energy saving alternative to the halogen G4
- The size is best fit into intricate or compact luminaires or chandeliers, creating the desired atmosphere instantly
- High efficacy of up to 150lm/W



12V

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Non-Dimmable										
EU205011-0Pv00	G4	1.1	120	2700K	80	15000	L11 x W13 x H36	F	Econ	1
EU205012-0Pv00	G4	1.2	180	2700K	80	15000	L11 x W13 x H36	D	Econ	1
EU205015-0Pv00	G4	1.5	220	2700K	80	15000	L11 x W13 x H36	D	Econ	1
EU203010-CSv00	G4	1.0	100	2700K	80	15000	Ø10 x 34	F	Econ	2
EU204017-CSv00	G4	1.7	180	2700K	80	15000	Ø10 x 40	F	Econ	3
EU204017-CSv01	G4	1.7	250	2700K	80	15000	Ø10 x 40	D	Econ	3

G9/GU9





Product Features

- MEGAMAN® LED G9/GU9 is the easy retrofit to halogen G9 with its highly luminous efficacy and dimmable option
- Dimmable and non-dimmable versions available
- Expansion of the product range with high lumen output up to 800lm
- High efficacy of up to 150 lm/W
- Long lifetime up to 25,000 hours

220-240V



Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable											
LU215025/dm-OPv00 NEW	G9	2.5	350	2700K	80	25000	Ø16 x 52	100-10%	D	Smart	1
LU207036/dm-OPv00	GU9	3.6	400	2700K	80	25000	Ø18 x 56	100-10%	E	Smart	2
LU207036/dm-CSv00	GU9	3.6	450	2700K	80	25000	Ø18 x 56	100-10%	D	Smart	3
LU209040/dm-OPv00	GU9	4	470	2700K	80	15000	Ø19 x 54	100-10%	E	Smart	4
LU209040/dm-CSv00	GU9	4	500	2700K	80	15000	Ø19 x 54	100-10%	E	Smart	5
LU210055/dm-OPv00	GU9	5.5	650	2700K	80	15000	Ø19 x 60	100-10%	E	Smart	6
LU210055/dm-CSv00	GU9	5.5	680	2700K	80	15000	Ø19 x 60	100-10%	E	Smart	7
LU211070/dm-OPv00	GU9	7	730	2700K	80	15000	Ø19 x 75	100-10%	F	Smart	8
LU211070/dm-CSv00	GU9	7	800	2700K	80	15000	Ø19 x 75	100-10%	E	Smart	9
Non-Dimmable											
LU204021-CSv00	G9	2.1	180	2700K	80	15000	Ø19 x 43	N/A	F	Econ	10
LU212015-OPv00	G9	1.5	200	2700K	80	15000	Ø16 x 46	N/A	E	Econ	11
LU212020-OPv00	G9	2	280	2700K	80	15000	Ø16 x 46	N/A	D	Econ	11
LU214025-OPv00 NEW	G9	2.5	350	2700K	80	15000	Ø16 x 46	N/A	D	Econ	12

-OPv00: Opal Appearance
-CSv00: Clear Appearance

CROWN SILVER





Product Features

- MEGAMAN LED Crown Silver, Black and Gold with the unique plated crown top and clear light bulb finishing
- Crown Silver, Black and Gold are the best flawless mirror lighting and decorative lighting with an aesthetic
- High efficacy of up to 113lm/W
- Up to 88% instant energy saving compared to traditional light bulbs



220-240V

Lamp Type	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable													
Crown Silver													
P45	LS203040/dm-CSv00	NEW	E14	4	380	2700K	80	15000	Ø45 x 84	100-10%	F	Smart	1
A60	LS202040/dm-CSv00	NEW	E27	4	380	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
A60	LS202075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
G95	LS208075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø95 x 135	100-10%	F	Smart	3
G125	LS211075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø125 x 168	100-10%	F	Smart	4



Lamp Type	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable													
Crown Gold													
P45	LS205040/dm-CSv00	NEW	E14	4	380	2700K	80	15000	Ø45 x 84	100-10%	F	Smart	1
A60	LS207040/dm-CSv00	NEW	E27	4	380	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
A60	LS207075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
G95	LS210075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø95 x 135	100-10%	F	Smart	3
G125	LS213075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø125 x 168	100-10%	F	Smart	4

CROWN SILVER





Product Features

- MEGAMAN LED Crown Silver, Black and Gold with the unique plated crown top and clear light bulb finishing
- Crown Silver, Black and Gold are the best flawless mirror lighting and decorative lighting with an aesthetic
- High efficacy of up to 113lm/W
- Up to 88% instant energy saving compared to traditional light bulbs



220-240V

Lamp Type	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable													
Crown Black													
P45	LS204040/dm-CSv00	NEW	E14	4	380	2700K	80	15000	Ø45 x 84	100-10%	F	Smart	1
A60	LS206040/dm-CSv00	NEW	E27	4	380	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
A60	LS206075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø60 x 105	100-10%	F	Smart	2
G95	LS209075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø95 x 135	100-10%	F	Smart	3
G125	LS212075/dm-CSv00	NEW	E27	7.5	850	2700K	80	15000	Ø125 x 168	100-10%	F	Smart	4

SMOKY FILAMENT





Product Features

- Ultra-warm 1800K colour temperature delivers a soft, vintage-inspired glow, creating a cosy and relaxing atmosphere
- Designed for ambience rather than task lighting, enhancing warmth and comfort in any space
- Elegant smoky glass creates a sophisticated, contemporary look - even when switched off
- Offered in A60, G95, G125 and ST64 lamp shape to suit various decorative pendants and exposed-bulb designs
- Produces a candle-like, intimate atmosphere - perfect for hospitality, residential and mood lighting applications



220-240V

Lamp Type	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Series	Photo
Non-Dimmable												
A60	LG325040-GYv00	NEW	E27	4	140	1800K	80	15000	Ø60 x 105	N/A	Econ	1
G95	LG326040-GYv00	NEW	E27	4	140	1800K	80	15000	Ø95 x 135	N/A	Econ	2
G125	LG327040-GYv00	NEW	E27	4	140	1800K	80	15000	Ø125 x 168	N/A	Econ	3
ST64	LG328040-GYv00	NEW	E27	4	140	1800K	80	15000	Ø64 x 143	N/A	Econ	4

LED T5 TUBE





Product Features

- Perfect replacement of existing T5 fluorescent lamps operating on AC mains power connection without any energy loss from the electronic ballast
- High efficacy up to 150lm/W
- Extra-long lifetime of up to 50 000 hours
- Wide voltage operation AC/DC 186V to 260V
- Shatterproof versions available with special PET coating

Remove the electronic ballast before connection.



Remove the electronic ballast before connection.



220-240V **AC/DC Input**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp. (CRI)	CRI	Rated Life (hrs)	Dimension (mm)	Power Factor (λ)	Energy Label	Series
LT201075/ac-06v00	G5	7.5	1000/1100/1100	133/147/147	3000/4000/6500K	80	50000	Ø18 x 563	>0.9	E/D/D	Smart
LT201160/ac-12v00	G5	16	2200/2400/2400	138/150/150	3000/4000/6500K	80	50000	Ø18 x 1163	>0.9	D/D/D	Smart
LT201260/ac-12v00	G5	26	3600/3900/3900	138/150/150	3000/4000/6500K	80	50000	Ø18 x 1163	>0.9	D/D/D	Smart
LT201260/ac-15v00	G5	26	3600/3900/3900	138/150/150	3000/4000/6500K	80	50000	Ø18 x 1463	>0.9	D/D/D	Smart
LT201340/ac-15v00	G5	34	4600/5100/5100	138/150/150	3000/4000/6500K	80	50000	Ø18 x 1463	>0.9	D/D/D	Smart

Compatible With Emergency Module

Remove the electronic ballast before connection.



Remove the electronic ballast before connection.



LA11190
LA11193 (Self-Test)



LA11199
LA11200 (Self-Test)



LED T5 TUBE





Product Features

- Perfect replacement of existing T5 fluorescent lamps on electronic ballast installations without rewiring
- Compatible with large number of electronic ballast in the market
- High efficacy of up to 153 lm/W
- Extra-long lifetime of 50,000 hours
- Low Flickering Ratio ≤ 8%
- IEC 62776 compliance (Double-capped LED lamps designed to retrofit linear fluorescent lamps – Safety Specification)

Electronic Ballast

Eq. Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp. (CRI)	Rated Life (hrs)	Dimension (mm)	Power Factor (λ)	Energy Label	Series
14	LT201075/eb-06v00	G5	7.5	1000/1100/1100	133/147/147	3000K/4000K/6500K	50000	Ø18 x 563	>0.9	E/D/D	Smart
28	LT201160/eb-12v00	G5	16	2200/2400/2400	138/150/150	3000K/4000K/6500K	50000	Ø18 x 1163	>0.9	E/D/D	Smart
54	LT201260/eb-12v00	G5	26	3600/3900/3900	138/150/150	3000K/4000K/6500K	50000	Ø18 x 1163	>0.9	E/D/D	Smart
35	LT201190/eb-15v00	G5	19	2650/2900/2900	139/153/153	3000K/4000K/6500K	50000	Ø18 x 1463	>0.9	E/D/D	Smart
49	LT201260/eb-15v00	G5	26	3600/3900/3900	138/150/150	3000K/4000K/6500K	50000	Ø18 x 1463	>0.9	E/D/D	Smart
80	LT201370/eb-15v00	G5	37	5100/5600/5600	138/151/151	3000K/4000K/6500K	50000	Ø18 x 1463	>0.9	E/D/D	Smart

* Please refer to page 68 to 69 for the compatibility list.

LED T8 TUBE





Product Features

- Smooth appearance and even light distribution achieved by wide exit window
- Quick and simple retrofit replacement of existing T8 fluorescent lamps on magnetic ballast installations without rewiring
- High efficacy up to 210lm/W
- Up to Energy Class A
- Instant and significant energy savings
- Extra-long lifetime up to 100,000 hours
- Wide voltage operation AC/DC 186V to 260V
- Shatterproof versions available with special PET coating

220-240V | **AC/DC Input** | **Magnetic Ballast Compatible**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Power Factor (λ)	Series
Professional series : 210lm/W, Class A											
LT205055/mb-06v04	G13	5.5	1155	210	4000K	80	100000	Ø28 x 603	A	≥ 0.9	Pro
LT205090/mb-09v04	G13	9	1890	210	4000K	80	100000	Ø28 x 908	A	≥ 0.9	Pro
LT205120/mb-12v04	G13	12	2520	210	4000K	80	100000	Ø28 x 1212	A	≥ 0.9	Pro
LT205175/mb-15v04	G13	17.5	3675	210	4000K	80	100000	Ø28 x 1513	A	≥ 0.9	Pro
Professional series : 185lm/W, Class B											
LT205062/mb-06v06	G13	6.2	1150/1150	185/185	4000K/6500K	80	75000	Ø28 x 603	B	≥ 0.5	Pro
LT205062/mb-06v04	G13	6.2	1150/1150	185/185	4000K/6500K	80	75000	Ø28x603	B	≥ 0.9	Pro
LT205135/mb-12v06	G13	13.5	2500/2500	185/185	4000K/6500K	80	75000	Ø28 x 1212	B	≥ 0.5	Pro
LT205135/mb-12v04	G13	13.5	2500/2500	185/185	4000K/6500K	80	75000	Ø28 x 1212	B	≥ 0.9	Pro
LT205200/mb-15v06	G13	20	3700/3700	185/185	4000K/6500K	80	75000	Ø28 x 1513	B	≥ 0.5	Pro
LT205200/mb-15v04	G13	20	3700/3700	185/185	4000K/6500K	80	75000	Ø28 x 1513	B	≥ 0.9	Pro
LT205220/mb-18v06	G13	22	4100/4100	186/186	4000K/6500K	80	75000	Ø28 x 1779	B	≥ 0.5	Pro
LT205220/mb-18v04	G13	22	4100/4100	186/186	4000K/6500K	80	75000	Ø28 x 1779	B	≥ 0.9	Pro

SINGLE ENDED INPUT

If magnetic ballast and starter are available, wiring method is shown below.



If magnetic ballast and starter are NOT available, wiring method is shown below.



If magnetic ballast and starter are NOT available, wiring method is shown below.



LED T8 TUBE



220-240V **AC/DC Input** **Magnetic Ballast Compatible**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Power Factor (λ)	Series
Smart series : ≥150lm/W, Class D											
LT205065/mb-06v05	G13	6.5	900/1000/1000	138/154/154	3000/4000K/6500K	80	50000	Ø28 x 603	D	≥ 0.5	Smart
LT205065/mb-06v01	G13	6.5	900/1000/1000	138/154/154	3000/4000K/6500K	80	50000	Ø28 x 603	D	≥ 0.9	Smart
LT205105/mb-09v05	G13	10.5	1450/1600/1600	138/152/152	3000/4000K/6500K	80	50000	Ø28 x 908	D	≥ 0.5	Smart
LT205105/mb-09v01	G13	10.5	1450/1600/1600	138/152/152	3000/4000K/6500K	80	50000	Ø28 x 908	D	≥ 0.9	Smart
LT205160/mb-12v05	G13	16	2200/2400/2400	138/150/150	3000/4000K/6500K	80	50000	Ø28 x 1212	D	≥ 0.5	Smart
LT205160/mb-12v01	G13	16	2200/2400/2400	138/150/150	3000/4000K/6500K	80	50000	Ø28 x 1212	D	≥ 0.9	Smart
LT205240/mb-15v05	G13	24	3300/3600/3600	138/150/150	3000/4000K/6500K	80	50000	Ø28 x 1513	D	≥ 0.5	Smart
LT205240/mb-15v01	G13	24	3300/3600/3600	138/150/150	3000/4000K/6500K	80	50000	Ø28 x 1513	D	≥ 0.9	Smart
LT205245/mb-18v05	G13	24.5	3500/3800/3800	143/155/155	3000/4000K/6500K	80	50000	Ø28 x 1779	D	≥ 0.5	Smart
LT205245/mb-18v01	G13	24.5	3500/3800/3800	143/155/155	3000/4000K/6500K	80	50000	Ø28 x 1779	D	≥ 0.9	Smart
Econ series : ≥123lm/W, Class E											
LT205090/mb-06v03	G13	9	1000/1150/1150	111/128/128	3000/4000K/6500K	80	30000	Ø28 x 603	E	≥ 0.5	Econ
LT205090/mb-06v00	G13	9	1000/1150/1150	111/128/128	3000/4000K/6500K	80	30000	Ø28 x 603	E	≥ 0.9	Econ
LT205125/mb-09v03	G13	12.5	1450/1600/1600	116/128/128	3000/4000K/6500K	80	30000	Ø28 x 908	E	≥ 0.5	Econ
LT205125/mb-09v00	G13	12.5	1450/1600/1600	116/128/128	3000/4000K/6500K	80	30000	Ø28 x 908	E	≥ 0.9	Econ
LT205160/mb-12v03	G13	16	1850/2000/2000	116/125/125	3000/4000K/6500K	80	30000	Ø28 x 1212	E	≥ 0.5	Econ
LT205160/mb-12v00	G13	16	1850/2000/2000	116/125/125	3000/4000K/6500K	80	30000	Ø28 x 1212	E	≥ 0.9	Econ
LT205220/mb-15v03	G13	22	2500/2700/2700	114/123/123	3000/4000K/6500K	80	30000	Ø28 x 1513	E	≥ 0.5	Econ
LT205220/mb-15v00	G13	22	2500/2700/2700	114/123/123	3000/4000K/6500K	80	30000	Ø28 x 1513	E	≥ 0.9	Econ
LT205245/mb-18v03	G13	24.5	2900/3100/3100	118/126/126	3000/4000K/6500K	80	30000	Ø28 x 1779	E	≥ 0.5	Econ
LT205245/mb-18v00	G13	24.5	2900/3100/3100	118/126/126	3000/4000K/6500K	80	30000	Ø28 x 1779	E	≥ 0.9	Econ

Compatible With
Emergency Module

Remove the electronic ballast before connection.



Remove the electronic ballast before connection.



LA11190
LA11193 (Self-Test)



LA11199
LA11200 (Self-Test)



LED T8 TUBE
Microwave Motion Sensor







Product Features

- Automatically dimmed from 100% to 2W light output
- Motion detection radius up to five meters
- Excellent energy-savings thanks to the use of an intelligent microwave motion sensor
- Quick and simple retrofit replacement of existing T8 fluorescent lamps on magnetic ballast installations without rewiring
- High efficacy up to 150lm/W
- Stays on for 30 seconds after movement is detected
- Energy Class D
- Extra-long lifetime up to 50,000 hours
- Wide voltage operation AC/DC 186V to 260V
- Shatterproof versions available with special PET coating

220-240V | **AC/DC Input** | **Magnetic Ballast Compatible**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Power Factor (λ)	Series
Smart series : ≥150lm/W, Class D											
LT205060/mb/ms-06v05	G13	6	810/900/900	135/150/150	3000/4000/6500K	80	50000	Ø28 x 603	D	≥ 0.5	Smart
LT205060/mb/ms-06v01	G13	6	810/900/900	135/150/150	3000/4000/6500K	80	50000	Ø28 x 603	D	≥ 0.9	Smart
LT205120/mb/ms-12v05	G13	12	1620/1800/1800	135/150/150	3000/4000/6500K	80	50000	Ø28 x 1212	D	≥ 0.5	Smart
LT205120/mb/ms-12v01	G13	12	1620/1800/1800	135/150/150	3000/4000/6500K	80	50000	Ø28 x 1212	D	≥ 0.9	Smart
LT205180/mb/ms-15v05	G13	18	2500/2700/2700	139/150/150	3000/4000/6500K	80	50000	Ø28 x 1513	D	≥ 0.5	Smart
LT205180/mb/ms-15v01	G13	18	2500/2700/2700	139/150/150	3000/4000/6500K	80	50000	Ø28 x 1513	D	≥ 0.9	Smart
LT205200/mb/ms-18v05	G13	20	2900/3100/3100	145/155/155	3000/4000/6500K	80	50000	Ø28 x 1513	D	≥ 0.5	Smart
LT205200/mb/ms-18v01	G13	20	2900/3100/3100	145/155/155	3000/4000/6500K	80	50000	Ø28 x 1513	D	≥ 0.9	Smart







Compatible With
Emergency Module

Remove the electronic ballast before connection.



Remove the electronic ballast before connection.



LA11190
LA11193 (Self-Test)



* GTM range also available, please refer to page 78.

LED PLUG-IN TUBE





Product Features

- Easy plug-and-play installation without any additional wiring
- Direct retrofit replacement of existing compact fluorescent lamps
- Durable polycarbonate construction
- No toxic chemicals such as mercury which could be released with broken fluorescent lamps
- Energy Class D
- Life time up to 30,000 hours
- Rotatable base around its longitudinal axis (± 90°) for G24d-1, G24d-2 and G24d-3
- Delivers an expansive 120° beam angle, providing broader light coverage and enhanced visual comfort in any setting



220-240V **AC Main** **Magnetic Ballast Compatible**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Non-Dimmable											
LP202030-0Pv00	G23	3	410	137	3000K	80	30000	L32 x W21 x H166	D	Econ	1
LP202040-0Pv00	G23	4	550	138	3000K	80	30000	L32 x W21 x H166	D	Econ	1
LP203055-0Pv00	G23	5.5	760	138	3000K	80	30000	L32 x W21 x H236	D	Econ	2
LP204060-0Pv00 NEW	G24d-1	6	600/660	100/110	3000K/4000K	80	30000	Ø33 x H122	F/E	Econ	3
LP204070-0Pv00 NEW	G24d-2	7	700/770	100/110	3000K/4000K	80	30000	Ø33 x H122	F/E	Econ	3
LP204100-0Pv00 NEW	G24d-3	10	990/1100	100/110	3000K/4000K	80	30000	Ø33 x H137	F/E	Econ	4



LP204070-OPv00 (G24d-1)



LP204070-OPv00 (G24d-2)



LP204070-OPv00 (G24d-3)

NIGHT LIGHT





Product Features

- Night Light series is designed to bring convenience, safety, and style to any home
- A smart choice for modern living providing a gentle glow in the dark, enhancing child's room or simply saving energy
- Perfect for bedrooms, hallways, bathrooms, or any space that needs a touch of illumination without the hassle of switching lights on and off
- Plug & play sockets version and battery-operated version available

Night Light with PIR Motion Sensor

Detecting movement within a specific range, activating the light instantly for convenience and safety, turning it off after a set period of inactivity to ensure it's only on when needed.

Night Light with Day/Night Sensor

Adjusting to ambient light levels, automatically switching on at dusk and off at dawn.

220-240V

EU Plug version













Model No.	Wattage (W)	Luminous Flux (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Series	Photo
Day Night Sensor								
NL201030/sr-v00	0.3	5 (3000K) 6 (6500K)	3000K/6500K	80	25000	L90 x W60 x H53.5	Smart	1
NL202030/sr-v00	0.3	3 (3000K) 4 (6500K)	3000K/6500K	80	25000	L60 x W60 x H69	Smart	2
NL203020/sr-v00	0.2	2 (3000K) 3 (6500K)	3000K/6500K	80	25000	L55 x W48 x H59	Smart	3
NL209020/sr-v00	0.2	2 (3000K) 3 (6500K)	3000K/6500K	80	25000	L37 x W74 x H105	Smart	4
Day Night Sensor & Motion Sensor								
NL204060/pr/sr-v00	0.6	18 (3000K) 19 (6500K)	3000K/6500K	80	25000	L62 x W62 x H64.5	Smart	5
NL208035/pr/sr-v00	0.35	5 (3000K) 6 (6500K)	3000K/6500K	80	25000	Ø60 x H58	Smart	6

3*AAA (excluded)

Battery version







Model No.	Wattage (W)	Luminous Flux (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Series	Photo
Day Night Sensor & Motion Sensor								
NL301030/pr/sr-v00	0.3	10	3000K/6500K	80	25000	L80 x W80 x H28	Smart	7
NL302040/pr/sr-v00	0.4	2	3000K/6500K	80	25000	L65 x W62 x H22	Smart	8
NL303025/pr/sr-v00	0.25	10	3000K/6500K	80	25000	L86 x W69 x H36	Smart	9

NIGHT LIGHT





Product Features

- Night Light series is designed to bring convenience, safety, and style to any home
- A smart choice for modern living providing a gentle glow in the dark, enhancing child's room or simply saving energy
- Perfect for bedrooms, hallways, bathrooms, or any space that needs a touch of illumination without the hassle of switching lights on and off
- Plug & play sockets version and battery-operated version available

Night Light with PIR Motion Sensor

Detecting movement within a specific range, activating the light instantly for convenience and safety, turning it off after a set period of inactivity to ensure it's only on when needed.

Night Light with Day/Night Sensor

Adjusting to ambient light levels, automatically switching on at dusk and off at dawn.

150 Auto working time, assuming 5 times per day

USB-C

Rechargeable Version



Model No.	Wattage (W)	Luminous Flux (lm)	CCT	CRI	Rated Life (hrs)	Battery Volume (mAh)	Dimension (mm)	Series	Remarks	Photo
NL401035/pr/sr/rb-v00	0.35	10	2700K	80	25000	400	Ø60 x H25	Smart	Charging time: 2.5hours Working time : 8hours	1
NL402050/pr/sr/rb-v00	0.5	35	2700K	80	25000	1200	Ø105 x H24	Smart	Charging time: 3.5hours Working time : 11hours	2
NL403035/pr/sr/rb-v00	0.35	8	2700K	80	25000	400	Ø63 x 64	Smart	Charging time: 2.5hours Working time : 8hours	3
NL404080/pr/sc/sr/rb-v00	0.8	30	2700K	80	25000	750	Ø86 x 15	Smart	Charging time: 1.5hours Working time : 6.5hours	4
NL405080/pr/sc/sr/rb-v00	0.8	30	2700K	80	25000	750	75 x 81 x 15	Smart	Charging time: 1.5hours Working time : 6.5hours	5
NL407145/pr/sc/sr/rb-v00	1.45	45	2700K	80	25000	1200	Ø95 x 26	Smart	Charging time: 2hours Working time : 7hours	6
NL408145/pr/sc/sr/rb-v00	1.45	20	2700K	80	25000	1200	Ø95 x 26	Smart	Charging time: 2hours Working time : 6hours	7



NIGHT LIGHT





Product Features

- Battery is detachable and replaceable
- Magnet + metal piece mounting holder
- Linkable

When people passes by any PIR controller, all the other night lights will light up together.



160 Auto working time, assuming 5 times per day

SENSOR Light PIR Sensor Switching CCT



USB-C

Rechargeable Version

Model No.	Wattage (W)	Luminous Flux (lm)	CCT	CRI	Rated Life (hrs)	Battery Volume (mAh)	Dimension (mm)	Series	Remarks
NL406080/pr/sc/sr/rb-v00	0.8	160	2700K	80	25000	1000	111x45x18.6	Smart	Charging time: 1.5hours Working time : 9hours

- Press & hold (2s): ON/OFF
- Press to switch modes:
  Full on / Sensor on / PIR & Light sensor on

Press to cycle through:
Uplight / Downlight / Dual-direction light



Touch to change
CCT & dimming

CLUSTERLITE®





MEGAMAN® LED CLUSTERLITE® is specifically designed to replace Mercury tungsten blended lamps and metal halide lamps used in commercial and industrial areas. MEGAMAN® LED CLUSTERLITE® has phenomenal attributes compared to high pressure discharge lamps; including high lumen maintenance, even light distribution, good colour rendering, high colour uniformity, negligible colour shift and excellent energy-savings.

Product Features

- Quick and simple retrofit replacement of High-Intensity Discharge (HID) lamps on existing EM ballast or mains connection
- Compact tubing design for maximum lumen output
- Extremely high lumen output of up to 11,500 lm
- High efficacy of up to 171lm/W with Energy Class C
- Lifetime 50,000 hours
- 6kV surge protection
- Free of harmful UV and radioactive Kr85
- Option of 2000K version available for Sodium lamp replacement



220-240V

6kV SURGE PROTECTION

Model No.	Lamp Base	Wattage (W)	Luminous Flux (lm)	Colour Temp.	CRI	Rated Life (hrs)	Operating Temperature	Dimension (mm)	Energy Label	Series	Photo
Passive Cooling											
LH200018-OPv00	E27	18.5	2800 (2700K) 3000 (4000K)	2700K/4000K	80	50000	-30ºC to +60ºC	Ø63 x 196	D (2700K) C (4000K)	Pro	1
LH200024-OPv00	E27	24.5	2900 (2000K) 4000 (2700K) 4200 (4000K)	2000K 2700K/4000K	80	50000	-30ºC to +60ºC	Ø63 x 196	E (2000K) C (2700K/4000K)	Pro	1
LH200033-OPv00	E27	33	4800 (2700K) 5300 (4000K)	2700K/4000K	80	50000	-30ºC to +60ºC	Ø63 x 217	D	Pro	2
Active Cooling											
LH201080-OPv00	E27/E40	80	11000 (2700K) 11500 (4000K)	2700K/4000K	80	50000	-30ºC to +40ºC	Ø80 x 252 (E27) Ø80 x 265 (E40)	D	Pro	3

The LED CLUSTERLITE® is not water resistant. The waterproof performance of the lamp would only be attained if the lamp is used with a light fitting with an IP rating of IP44 or above.
The ambient temperature inside the fixture must not exceed 60°C, which is equivalent to a minimum volume of 120x360x220(mm).
The ambient temperature for LH201080-OPv00 inside the fixture must not exceed 40ºC, which is equivalent to a minimum volume of 580x580x400(mm)

LED HID ULTRA





Product Features

- Quick and simple retrofit replacement of High-Intensity Discharge (HID) lamps on existing EM ballast or mains connection
- High efficiency up to166lm/W & energy class up to C to maximize energy savings
- Wide wattage range from 13W to 60W, delivering from 1800lm to 9000lm
- Power factor >0.9 with 2kV surge protection
- Working temperature from -20ºC to +50ºC
- Long lifespan up to 25,000hrs


1


2


3


4

220-240V

Eq. Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Diameter (mm)	Energy Label	Series	Photo
Non-Dimmable												
70W	LG500130-0Pv00	NEW	E27	13	1800/2000	2700K/4000K	80	25000	Ø75 x 151	D	Smart	1
100W	LG500200-0Pv00	NEW	E27	20	2700/3000	2700K/4000K	80	25000	Ø75 x 151	D	Smart	1
150W	LG501240-0Pv00	NEW	E27	24	3600/4000	2700K/4000K	80	25000	Ø90 x 217	D (2700K) C (4000K)	Smart	2
250W	LG501380-0Pv00	NEW	E27	38	5400/6000	2700K/4000K	80	25000	Ø90 x 217	D	Smart	2
250W	LG502380-0Pv00	NEW	E40	38	5400/6000	2700K/4000K	80	25000	Ø90 x 202	D	Smart	3
400W	LG503600-0Pv00	NEW	E40	60	8100/9000	2700K/4000K	80	25000	Ø120 x 260	D	Smart	4

LED HID T-LINE





Product Features

- Quick and simple retrofit replacement of High-Intensity Discharge (HID) lamps on existing EM ballast or mains connection
- High efficiency up to 192lm/W & energy class up to (B) to maximize energy savings
- High lumen output up to 7500lm
- Power factor >0.9 with 2kV surge protection
- Working temperature from -20ºC to +50ºC
- Long lifespan up to 25,000hrs



220-240V

Eq. Watt (W)	Model No.		Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Diameter (mm)	Energy Label	Series	Photo
Non-Dimmable												
150W	LG504210-CSv00	NEW	E27	21	3600/4000	2700K/4000K	80	25000	Ø38 x 170	B	Smart	1
250W	LG505260-CSv00	NEW	E27	26	4500/5000	2700K/4000K	80	25000	Ø38 x 210	B	Smart	2
400W	LG505410-CSv00	NEW	E40	41	7000/7500	2700K/4000K	80	25000	Ø46 x 225	C	Smart	3

PLANT LAMP





Product Features

- MEGAMAN® LED Plant Lamp series is an eco-friendly solution for horticulture lighting to assist plants in the photosynthesis process without adding extra heat, which can increase the plant yield
- Up to IP55, protecting the light source from water and dust
- More control over cultivation with custom light recipes, to meet specific needs of specific crops
- Tailored light spectrum for enhance nutritional value and quantity
- Sustainable crop cultivation for shorter growth cycles and healthier crop growth



1



2

220-240V

Lamp Type	Model No.	Wattage (W)	Beam Angle (°)	Lamp Base	Dimension (mm)	Rated Life (hrs)	Photon Flux (umol/s)	Photon Flux per Watt (µmol/J)	IP Rating	Series	Photo
Non-Dimmable											
PAR38	LR242160/pt-HRv00	12	35	E27	Ø121 x 132	25000	24	2.0	IP55	Smart	1
A60	LG072085/pt-OPv00	8.5	N/A	E27	Ø60 x 110	25000	18	2.1	IP20	Smart	2

MEGAMAN® HORTICULTURE LIGHTING

Important Segments for Horticulture Lighting

- Ceiling Lighting



- Multilayer Cultivation



Plant	Visible Light Spectrum	Effect on Plant	Reference
Cabbage	660nm (Red)	Increased anthocyanin content	1
Baby Leaf Lettuce	658nm (Red)	Phenolics concentration increased by 6%	2
Tomato	660nm (Red)	Increased tomato yield	3
Kale Plants	640nm (Red)	Lutein and chlorophyll a, b accumulation increased	4
Lettuce	638nm (Red)	Increased vitamin C content in mustard, spinach and green onions	5
Green Onions	638nm (Red)	Reduction of nitrate content	

Reference:
1. www.actahort.org/books/907/907_25.htm
2. www.sciencedirect.com/science/article/pii/S00988472090013483
3. www.jstage.jst.go.jp/article/ecb/50/1/50_63/_article
4. hortsci.ashspublications.org/content/43/7/2243.abstract
5. hortsci.ashspublications.org/content/44/7/1857.full



Artificial lighting is necessary because:

- Supplemental lighting
- Photoperiodic lighting
- Cultivation without daylight



SENSOR LIGHT





Product Features

- Equipped with an ingenious light sensor, the MEGAMAN® LED Sensor Light automatically lights up in darkness and turns itself off in a bright environment, helping to conserve energy
- Built-in sensors with front & back sensor design
- Automatic detection of surrounding brightness level with high sensitivity and wide range
- High efficacy of up to 165lm/W
- Low Flickering Ratio ≤ 8%


1


2


3

220-240V

SENSOR Light

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series	Photo
Standard Bulb										
Non-Dimmable										
LG7104.9r	E27	4.9	470	2700K	80	15000	Ø60 x 109	F	Smart	1
LG7108.8r	E27	8.8	810	2700K	80	15000	Ø60 x 109	F	Smart	1
LG7109.7r	E27	9.7	1055	2700K	80	15000	Ø60 x 109	F	Smart	1
Filament										
Non-Dimmable										
LG6104.2rCS	E27	4.2	470	2700K	80	15000	Ø60 x 104	E	Smart	2
LG9804.9rCS	E27	4.9	810	2700K	80	15000	Ø60 x 104	C	Smart	3

RADAR MOTION SENSOR LIGHT





With the combinations of the features of a daylight sensor and motion sensor detector, MEGAMAN® LED Radar Motion Sensor Light automatically lights up in darkness only when a person is passing by, continues to light up until the person leaves and turns itself off after a certain period of time.

Product Features

- Excellent energy-savings with the use of an intelligent microwave radar sensor to deactivate the motion sensor during the day and activate motion detection at night
- Automatic adjustment of working status and high sensitivity with a wide distance range. No more hunting for a switch
- Stays on for 60 seconds after movement is detected
- Lifetime of 25,000 hours
- Suitable applications include staircases, hallway, front door, storage room, garage, balcony, gate, etc
- Low Flickering Ratio ≤ 8%



220-240V

RADAR MOTION Sensor

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series
Non-Dimmable									
LG279049/ms/sr-0Pv00	E27	4.9	470	2700K	80	25000	Ø60 x 109	F	Smart
LG279075/ms/sr-0Pv00	E27	7.5	810	2700K	80	25000	Ø60 x 109	F	Smart













MICROWAVE MOTION SENSOR LIGHT





Product Features

- Provides an automatic stand-by dim function 20% for energy saving purpose
- The bulbs will only turn on when movement is detected which helps to conserve energy by ensuring that lights aren't left on unnecessarily in unoccupied area
- Ideal for workspaces, backyards, and other areas where desire a gentle background light continuously, but full brightness when required
- Stays on for 30 seconds after movement is detected
- Life time up to 25,000 hrs
- Flicker free to enhance eye comfort without fatigue



220-240V





Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series
Non-Dimmable									
LG298042/ms/sr-OPv01	E27	4.2	470	2700K	80	25000	Ø60 x 109	F	Smart
LG298073/ms/sr-OPv01	E27	7.3	810	2700K	80	25000	Ø60 x 109	F	Smart
LG298087/ms/sr-OPv01	E27	8.7	1055	2700K	80	25000	Ø60 x 109	F	Smart













HIGH TEMPERATURE LAMP





LED High Temperature Lamp is designed to withstand high ambient temperature up to 60°C. Compatible with small and enclosed outdoor fixture in high temperature environment.

Product Features

- Life time of 25,000 hours at 40°C ambient temperature
- Flicker Free ≤3%
- Work with both AC and DC (DC-Emergency-Systems in Germany)



1



2

220-240V **-30˚C to +60˚C**

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life at L70 B50 at Ta40ºC (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Dimmable												
60	LG7106dv3	E27	6	810	2700K	80	25000	Ø60 x 110	100-10%	D	Smart	2
Non-Dimmable												
40	LG7104.5v3	E27	4.5	470	2700K	80	25000	Ø60 x 109	N/A	F	Smart	1
60	LG7107v3	E27	7	810	2700K	80	25000	Ø60 x 109	N/A	E	Smart	1



Compatible with small and enclosed outdoor fixture in high temperature environment

COLD WEATHER LAMP





LED Cold Weather Lamp is specifically designed for the cold temperature conditions in Nordic countries. They can withstand the ambient temperatures down to -40ºC.

Product Features

- No less efficient and no shorten life span in freezing weather
- Light up immediately and give full light in temperature down to -40ºC
- Flicker Free ≤3%



220-240V | **-40˚C to +45˚C**

Eq.Watt (W)	Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Colour Temp.	CRI	Rated Life at L70 B50 at Ta40ºC (hrs)	Dimension (mm)	Dimmable	Energy Label	Series
Non-Dimmable											
60	LG7108.6v2	E27	8.6	810	2700K	80	15000	Ø60 x 109	N/A	F	Smart
75	LG7109.6v2	E27	9.6	1055	2700K	80	15000	Ø60 x 109	N/A	F	Smart



Value-for-money Product range

MEGAMAN®

Go-to-market

Experience of Go-to-market product range in emerging markets



GTM RANGE


1


2

220-240V

Lamp Type	Model No.	Wattage (W)	Max. Luminous Intensity (cd)	Beam Angle (°)	Lumen (lm)	Useful Lumen (lm)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Dimmable	Energy Label	Series	Photo
Non-Dimmable														
PAR16	LR222019-HRv00-WF	1.9	300	36	160	140	2700K	80	15000	Ø50 x 55	N/A	F	GTM	1
PAR16	LR222031-HRv00-WF	3.1	450	36	270	230	2700K	80	15000	Ø50 x 55	N/A	F	GTM	1
PAR16	LR222047-HRv00-WF	4.7	650	36	390	345	2700K	80	15000	Ø50 x 55	N/A	F	GTM	1
PAR16	LR232055-HRv00-WF	5.5	1050	36	630	540	2700K	80	15000	Ø50 x 55	N/A	E	GTM	2
PAR16	LR232065-HRv00-WF	6.5	1350	36	810	690	2700K	80	15000	Ø50 x 55	N/A	E	GTM	2



GTM RANGE

LED T8 TUBE

SINGLE ENDED INPUT

If magnetic ballast and starter are available, wiring method is shown below.



If magnetic ballast and starter are NOT available, wiring method is shown below.



If magnetic ballast and starter are NOT available, wiring method is shown below.



220-240V **AC/DC Input** **Magnetic Ballast Compatible**

Model No.	Lamp Base	Wattage (W)	Lumen (lm)	Lumen Efficacy (lm/W)	Colour Temp.	CRI	Rated Life (hrs)	Dimension (mm)	Energy Label	Series
LT205090/mb-06v02	G13	9	810/900/900	90/100/100	3000/4000/6500K	80	15000	Ø28 x 603	F	GTM
LT205140/mb-09v02	G13	14	1260/1400/1400	90/100/100	3000/4000/6500K	80	15000	Ø28 x 908	F	GTM
LT205180/mb-12v02	G13	18	1620/1800/1800	90/100/100	3000/4000/6500K	80	15000	Ø28 x 1212	F	GTM
LT205220/mb-15v02	G13	22	2000/2200/2200	90/100/100	3000/4000/6500K	80	15000	Ø28 x 1513	F	GTM



Compatible With **Emergency Module**

If magnetic ballast and starter are NOT available, wiring method is shown below.



If magnetic ballast and starter are NOT available, wiring method is shown below.



LA11190
LA11193 (Self-Test)



LA11199
LA11200 (Self-Test)



MEGAMAN® T5 SERIES
COMPATIBILITY LIST

LT201190/eb-15v00 I 1463mm I 19W I 2900lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
PHILIPS	HF-R 114-35 TL-5 EII	N/A	N/A	1	Yes
PHILIPS	HF-R 214-35 TL5 E11	N/A	N/A	2	Yes
PHILIPS	HF-S 235 TL5 II	N/A	N/A	2	Yes
OSRAM	QT-FIT5 1X14-35	N/A	N/A	1	Yes
OSRAM	QT-FIT5 2X14-35	N/A	N/A	2	Yes
OSRAM	QTP5 2*14-35	N/A	N/A	2	Yes
TRIDONIC	PC 2x14-35 T5 PRO lp	N/A	N/A	2	Yes

LT201260/eb-15v00 I 1463mm I 26W I 3900lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
PHILIPS	HF-S 149 TL5 II	N/A	N/A	1	Yes
PHILIPS	HF-S 249 TL5 II	N/A	N/A	2	Yes
OSRAM	QT-FIT5 1X49	N/A	N/A	1	Yes
OSRAM	QTP5 1X49	N/A	N/A	1	Yes
OSRAM	QTP5 2X49	N/A	N/A	2	Yes
OSRAM	QT-FIT5 2X49	N/A	N/A	2	Yes
TRIDONIC	PC 1X49 T5 TOP lp	N/A	N/A	1	Yes
TRIDONIC	PC 1/49 T5 INDUSTRY	N/A	N/A	1	Yes
TRIDONIC	PC 2/49 T5 INDUSTRY	N/A	N/A	2	Yes
TRIDONIC	PC 2X49 T5 TOP lp	N/A	N/A	2	Yes
TRIDONIC	PC 2X49 T5 PRO lp	N/A	N/A	2	Yes
BAG	BCS49.1FX-11/220-240	N/A	N/A	1	Yes
BAG	BCS49.2FX-11/220-240	N/A	N/A	2	Yes
Helvar	EL1X49ngn5	N/A	N/A	1	Yes

LT201370/eb-15v00 I 1463mm I 37W I 5600lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
PHILIPS	HF-P 2 80 TL5/PL-L III IDC	N/A	N/A	2	Yes
OSRAM	QTi 1X35/49/80/GII	N/A	N/A	1	Yes
OSRAM	QT-FQ 2X80	N/A	N/A	2	Yes
OSRAM	QTi 2X35/49/80/GII	N/A	N/A	2	Yes
TRIDONIC	PC 1X80 T5 PRO lp	N/A	N/A	1	Yes
TRIDONIC	PC 2/80 T5 INDUSTRY	N/A	N/A	2	Yes
TRIDONIC	PC 2X80 T5 PRO lp	N/A	N/A	2	Yes
BAG	BCS80.1FX-11/220-240	N/A	N/A	1	Yes
BAG	BCS80.2FX-11/220-240	N/A	N/A	2	Yes
Helvar	EL2X80ngn5	N/A	N/A	2	Yes
VS	ELXc 180.634	N/A	N/A	1	Yes

* MEGAMAN® has provided this ballast compatibility list for guidance when selecting a ballast and lamp combination.
The T5 tube were tested for compatibility with the below listed ballasts. Ballasts that do not appear on the chart might still be compatible but have not been tested.

MEGAMAN® T5 SERIES
COMPATIBILITY LIST

LT201075/eb-06v00 I 563mm I 7.5W I 1100lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
PHILIPS	HF-R 114-35 TL-5 EII	N/A	N/A	1	Yes
PHILIPS	HF-R 214-35 TL5 E11	N/A	N/A	2	Yes
OSRAM	QTP5 1X14-35	N/A	N/A	1	Yes
OSRAM	QTP5 2*14-35	N/A	N/A	2	Yes
OSRAM	QT-FIT5 2X14-35	N/A	N/A	2	Yes
TRIDONIC	PC 1/14-35/49/54 T5 PRO-M lp	N/A	N/A	1	Yes
TRIDONIC	PC 1/14-35/24/39 T5 PRO-M lp	N/A	N/A	1	Yes
TRIDONIC	PC 2x14-35 T5 PRO lp	N/A	N/A	2	Yes

LT201160/eb-12v00 I 1163mm I 16W I 2400lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
PHILIPS	HF-R 114-35 TL-5 EII	N/A	N/A	1	Yes
PHILIPS	HF-R 214-35 TL5 E11	N/A	N/A	2	Yes
OSRAM	QTP5 1X14-35	N/A	N/A	1	Yes
OSRAM	QT-FIT5 1X14-35	N/A	N/A	1	Yes
OSRAM	QT-FIT5 2X14-35	N/A	N/A	2	Yes
OSRAM	QTP5 2*14-35	N/A	N/A	2	Yes
TRIDONIC	PC 1X14-35 T5 PRO lp	N/A	N/A	1	Yes
TRIDONIC	PC 2x14-35 T5 PRO lp	N/A	N/A	2	Yes

LT201260/eb-12v00 I 1163mm I 26W I 3900lm

Brand	Model No.	Article No. / Ref No. / STK No.	EAN 10	Lamps on ballast	AC (50/60Hz) on HF Ballast Compatible
BAG	MLS80.1/54.2FR-11/220-240	10071609	N/A	1	Yes
BAG	MLS80.1FR-11/220-240	10071608	N/A	1	Yes
BAG	MF1/54, 55, 58 BAG-BCS54.FX	N/A	N/A	1	Yes
OSRAM	QTi 1X28/54/35/49 GII	4030027	4008321383358	1	Yes
OSRAM	QTi 2x28/54 DIM	4030254	4050300870717	2	Yes
OSRAM	QTi 2X28/54/35/49 GII	4030516	4008321383419	2	Yes
OSRAM	QT-FIT 5/8 2X54-58	4030291	4008321873842	2	Yes
OSRAM	QTP OPTIMAL 1X54-58	N/A	4008321873729	1	Yes
OSRAM	QTP OPTIMAL 2X54-58	4030271	4008321880253	2	Yes
OSRAM	MF 1/54-58 OSR-QTP-OPTI	4008321873729	N/A	1	Yes
OSRAM	1/54 OSR-QTP5-G2	N/A	N/A	1	Yes
OSRAM	QTP5II 1×54		4008321329394	1	Yes
PHILIPS	HF-P 154/155 TL5 HO/PL-L III IDC	86348200	872790086348200	1	Yes
PHILIPS	HF-P 254/255 TL5 HO/PL-L III IDC	86351200	872790086351200	2	Yes
PHILIPS	HF-Pi 1 28/35/49/54 TL-5 EII 220-240	91496530	871150091496530	1	Yes
PHILIPS	HF-R 254 TL5 EII 220-240	91008030	8711500910080	2	Yes
PHILIPS	HF-P 154 E2 III	N/A	N/A	1	Yes
PHILIPS	HF-P 154 TL5 E2	N/A	N/A	1	Yes
PHILIPS	HF-S 154 TL5	N/A	N/A	1	Yes
PHILIPS	HF-S 254 TL5	N/A	N/A	2	Yes
TRIDONIC	PCA 2x28/54 T5 EXCEL one4all lp	22176175	N/A	2	Yes
TRIDONIC	PC 2X54-T5 PRO lp	22185156	9006210250106	2	Yes
VS	ELXc 154.633	188946	N/A	1	Yes
VS	ELXc 254.636	188949	N/A	2	Yes
VS	1/54 VS-ELXC	N/A	N/A	1	Yes
HELVAR	1/54 HEL-EL-s-75°	N/A	N/A	1	Yes
HELVAR	EL 1×54S	N/A	N/A	1	Yes
HELVAR	1×54 NGN5	N/A	N/A	1	Yes

MEGAMAN®

Unit 1907, 19/F, Lu Plaza,
2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 2305 1722
Fax: (852) 2758 5957
Email: info@megaman.cc

www.megaman.cc

© Copyright 2026. All rights reserved by MEGAMAN®.
All information stated is correct at the time of printing and subject to changes without prior notice.

CA-LED-E-02026-02